



CONE G2 GU10 WHITE

Cone G2 is a neat, dimmable facade light with a cone-shaped design that delivers an even and pleasant asymmetrical light pattern on walls and ground. It is equally suitable for entrances, along facades, or garages in both private and public environments.

Light Technical Data

Built-in DIP switch (3000K/4000K) for color temperature adjustment. Reflector technology. Available with LED or GU10. The cone shape provides a light pattern that reaches further out on the ground. Ra>80.

Technical data

Built-in DIP switch for luminous flux adjustment. Replaceable LED and driver for easy servicing. Dimmable via phase dimming or DALI-2. LED lifetime: L80 100 000h Ta25°C. Driver lifetime: 100 000h /10%.

Operation and Connection

Color and material

Available in white, black, or galvanized steel, C4. The galvanized version develops a natural patina over time.

Measurement and installation

IP65, and galv IP44. The backplate mounts easily to the wall with double grommets for feed-through wiring. Prepared for surface-mounted cabling. Luminaire easily hangs in place afterwards, equipped with plug-in for smooth installation.

Controls

DESCRIPTION

GTIN:	7392971154497
Item Name:	Cone G2 GU10 White
Warranty:	5 years

LIGHT TECHNICAL DATA

Replaceability:	Replaceable LED by professional, Replaceable Control gear by professional
Lamp Holder (type):	GU10
Number of Lamps (pcs):	1
Life Time:	h Ta °C

TECHNICAL DATA

Voltage (type):

AC

OPERATION AND CONNECTION

Connection (type):

Quick Terminal

Connection (mm²):

5x0,75-2,5

Through Wiring:

Yes

Strain Relief:

No

Max. Power (W):

8

COLOR AND MATERIAL

Material:

Aluminium

Material Housing/Enclosure:

Aluminium, Plastic

Material Cover Ring:

Aluminium

Color:

White

Available in special color:

No

MEASUREMENT AND INSTALLATION

Operating Environment:

Indoor / damp locations, Indoor / dry locations, Indoor / wet

locations, Outdoor

IP Degree of Protection:

65

Protection Class:

II

Installation:

Wall

Mounting Installation:

Screw Mounting

Approval Marks:

a Hide-a-lite Choice, CE

Impact Strength:

IK08

Filament Test IEC 695-2-1(°C):

650

Length (mm):

147

Width (mm):

105

Height (mm):

123

Diameter (mm):

105

Weight (kg):

0,7

