



CONE G2 PILLAR SOCKET GU10 BLACK

Cone G2 Pillar is a dimmable bollard light featuring a cone-shaped luminaire that provides an even and pleasant asymmetrical light pattern on the ground. Perfect for pathways, gardens, and wooden decks in both private and public environments.

Light Technical Data

Reflector technology with built-in DIP switch (3000K/4000K) for easy color temperature adjustment. Available with LED or GU10. The cone shape provides a light pattern that reaches further out on the ground. $Ra > 80$.

Technical data

Built-in DIP switch for luminous flux adjustment. Replaceable LED and driver for easy servicing. Dimmable via phase dimming. LED lifetime: L80 100 000h Ta25°C. Driver lifetime: 100 000h /10%.

Operation and Connection

Pre-assembled with 2m cable for easy installation.

Color and material

Available in black or galvanized steel, C4. The galvanized version develops a natural patina over time. Available both with and without power outlet, socket.

Measurement and installation

IP65, socket IP44. Adapted for foundations, but also works on wooden decks or concrete slabs. Possibility to wire light and socket separately.

Controls

DESCRIPTION

GTIN:	7392971156064
Item Name:	Cone G2 Pillar Socket GU10 Black
Warranty:	5 years

LIGHT TECHNICAL DATA

Lamp Holder (type):	GU10
Number of Lamps (pcs):	1
Life Time:	h Ta °C

TECHNICAL DATA

Voltage (type):	AC
-----------------	----

OPERATION AND CONNECTION

Connection (type):	Quick Terminal
Connection (mm2):	5x0,75-2,5
Through Wiring:	Yes
Strain Relief:	No
THD (%):	20
Max. Power (W):	8

COLOR AND MATERIAL

Material:	Aluminium
Material Housing/Enclosure:	Aluminium
Material Cover Ring:	Aluminium
Color:	Black
Available in special color:	No

MEASUREMENT AND INSTALLATION

Operating Environment:	Outdoor
IP Degree of Protection:	54
Protection Class:	I
Installation:	Ground
Mounting Installation:	Screw Mounting
Impact Strength:	IK08
Filament Test IEC 695-2-1(°C):	650
Length (mm):	251
Width (mm):	160
Height (mm):	795
Diameter (mm):	105
Weight (kg):	3,7

