



CONVERTER FDIM G3 180MA

Mains dimmable driver for constant current luminaire 180mA. Push-in, loop-in, loop-out terminals for through wiring and screwless strain relief for cables from 0.5-2.5mm² on primary side, for cable/16mm flex hose. The secondary side has pre-wired cable and phono connector.

DESCRIPTION

GTIN:	7392971136349
Item Name:	Converter FDIM G3 180mA
Warranty:	5 years

LIGHT TECHNICAL DATA

Life Time Driver:	50 000h/10%
-------------------	-------------

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Trailing Edge, Leading Edge
Driver Model:	Constant Current
Driver Type:	Stand Alone
Connection (type):	Quick Terminal
Through Wiring:	Yes
Strain Relief:	Yes
Power Interval for Catalogue (W):	1-7,5
Max. Power (W):	7,5
Constant Current (mA):	180
Min. Ta (°C):	-20
Max. Ta (°C):	45
Max. Tc (°C):	75
Protection Against:	Short Circuit

COLOR AND MATERIAL

Material:	Plastic
Color:	White

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Surface mounted
Fire Safety Marks:	Not in insulation without protection cover
Approval Marks:	CE
Length (mm):	99
Width (mm):	45
Height (mm):	26
Weight (kg):	0,113

