hidealite | Elektro Elco AB Tallvägen 5, 564 35 Bankeryd, Sweden
Phone + 46(0)36 290 60 00 | info@elco.se | www.hidealite.com





LED-TRAFO SLT 12V 30W

DC transformer for 12V or 24V LED light sources. Protection against short circuiting, overloading and overheating with automatic restart.

DESCRIPTION

GTIN:	7392971131689
Item Name:	LED-trafo SLT 12V 30W
Warranty:	5 years

LIGHT TECHNICAL DATA

Life Time Driver:	35 000h/4%

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60

OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	OnOff
Driver Model:	Constant Voltage
Driver Type:	Stand Alone
Connection (type):	Screw Terminals
Connection (mm2):	2x0,75
Strain Relief:	Yes
Connection Secondary (type):	Screw Terminals
Secondary Connection (mm2):	2x0,75
Secondary Outputs (pair):	1
Power Interval for Catalogue (W):	0-30
Max. Power (W):	30
Standby Power:	0,3
Current (A):	0,16
Operating Temperature:	-20...+50°C
Max. Tc (°C):	90
Protection Against:	Short Circuit, Overheating 110°C, Overload
Fuse B10 (pcs):	24
Fuse B16 (pcs):	40
Fuse C10 (pcs):	40
Fuse C16 (pcs):	65

COLOR AND MATERIAL

Material:	Plastic
Color:	White
Environmental Assessment:	Byggvarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Built-in, Surface mounted
Mounting Installation:	Screw Mounting
Fire Safety Marks:	MM-mark
Approval Marks:	CE, S
Length (mm):	151
Width (mm):	40
Height (mm):	30
Weight (kg):	0,15



(mm)

