hidealite | Elektro Elco AB Tallvägen 5, 564 35 Bankeryd, Sweden
Phone + 46(0)36 290 60 00 | info@elco.se | www.hidealite.com





LED-DIMTRAFO DALI/PUSH 24V 30W

Powerful LED dimmer trafo for 12V or 24V LEDstrips. Perfect for dimming LEDstrip single color via Push (230V) Can also be dimmed via DALI Memory function which lights up with latest set value after power failure. For color control and further technical information see instruction manual.

DESCRIPTION

GTIN:	7392971136691
Item Name:	LED-dimtrafo DALI/PUSH 24V 30W
Warranty:	5 years

LIGHT TECHNICAL DATA

Life Time Driver:	50 000h/15%
Flicker (PstLM):	0,0346
Stroboscopic effect (SVM):	0,3389

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	180...260V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Push 230V, DALI 2, DALI DT6
Driver Model:	Constant Voltage
Driver Type:	Stand Alone
Connection (type):	Quick Terminal
Connection (mm2):	2x0,5-2,5
Strain Relief:	Yes
Connection Secondary (type):	Quick Terminal
Secondary Connection (mm2):	2x0,5-2,5
Power Factor λ:	0,93
Efficiency (%):	87
Power Interval for Catalogue (W):	1-30
Max. Power (W):	30
Standby Power:	1,5
Current (A):	1,25
Operating Temperature:	-25...+45°C
Max. Tc (°C):	85
Dimming secondary side:	PWM
Frequency PWM dimming (Hz):	>300
Memory Function Power Failure:	Yes
Protection Against:	Overheating 110°C, Overload
Fuse B10 (pcs):	35
Fuse B16 (pcs):	60
Fuse C10 (pcs):	40
Fuse C16 (pcs):	70

COLOR AND MATERIAL

Material:	Metal, Plastic
Color:	White
Environmental Assessment:	Byggvarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Fire Safety Marks:	MM-mark
Approval Marks:	CE, ENEC 25
Filament Test IEC 695-2-1(°C):	650
Length (mm):	170
Width (mm):	54
Height (mm):	28
Weight (kg):	0,2
Built-in Ø (mm):	60mm





(mm)

