



## STEPLIGHT GARDEN

Decorative step lighting with low energy consumption. Create striking staircase lighting, for example on patios and decks. Comes with 2×0.5 m rubber cables with screw connections. As an accessory there is also a transformer and 1 or 5 meter extension cables. Can be combined with Spotlight Garden and Decklight Garden thanks to the common coupling system.

### DESCRIPTION

<b>GTIN:</b>	7392971133140
<b>Item Name:</b>	Steplight Garden
<b>Warranty:</b>	5 years
<b>Type:</b>	.

### LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	3
<b>Light Source:</b>	LED
<b>Light Source Included:</b>	Yes
<b>Replaceability:</b>	Non-replaceable LED
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>80
<b>Colour Consistency (SDCM):</b>	3
<b>Light sharing:</b>	Asymmetric
<b>Light Outlet:</b>	Direct
<b>Number of Lamps (pcs):</b>	1
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	h Ta °C
<b>Nominal Life Time (h):</b>	50000
<b>Lumen maintenance 50 000h:</b>	L70
<b>LLMF @ 50 000h:</b>	0.7

## TECHNICAL DATA

Voltage (type):	DC
Voltage Interval (V):	12...12V
Voltage Nominal (V):	12
Voltage Forward (Vf):	9
Max. Power Luminaire (W):	0,8
Max. System Power (W):	0,8

## OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	OnOff
Driver Included:	No
Driver Model:	Constant Voltage
Connection (type):	Screw Connection, Cable
Length Connection (cm):	50
Connection (mm2):	2x0,5
Through Wiring:	Yes
Min. Ta (°C):	-25
Max. Ta (°C):	45
Max. Tc (°C):	80

## COLOR AND MATERIAL

Material:	Aluminium
Color:	Aluminum

## MEASUREMENT AND INSTALLATION

Operating Environment:	Outdoor
IP Degree of Protection:	67
Protection Class:	III
Installation:	Built-in
Mounting Installation:	Tension Spring
Max. Pressure (kg):	100
Approval Marks:	CE
Height (mm):	34
Diameter (mm):	36
Weight (kg):	0,07
Min. Built-in (mm):	Ø28x25
Height Recessed Part (mm):	23
Height Exterior Part (mm):	13
Built-in Ø (mm):	28mm

