



STEPLIGHT GARDEN

Decorative step lighting with low energy consumption. Create striking staircase lighting, for example on patios and decks. Comes with 2x0.5 m rubber cables with screw connections. As an accessory there is also a transformer and 1 or 5 meter extension cables. Can be combined with Spotlight Garden and Decklight Garden thanks to the common coupling system.

DESCRIPTION

| | |
|-------------------|------------------|
| GTIN: | 7392971133140 |
| Item Name: | Steplight Garden |
| Warranty: | 5 years |

LIGHT TECHNICAL DATA

| | |
|-------------------------------------|---------------------|
| Max. Luminaire Lumen (lm): | 3 |
| Light Source: | LED |
| Light Source Included: | Yes |
| Replaceability: | Non-replaceable LED |
| LED Colour: | Warm White |
| Colour Temperature (K): | 3000 |
| Colour Rendering Index (Ra): | >80 |
| Colour Consistency (SDCM): | 3 |
| Light sharing: | Asymmetric |
| Light Outlet: | Direct |
| Number of Lamps (pcs): | 1 |
| Number of LED (pcs): | 1 |
| Life Time: | L70 50000h Ta 25°C |
| Nominal Life Time (h): | 50000 |
| Lumen maintenance 50 000h: | L70 |
| LLMF @ 50 000h: | 0.7 |

TECHNICAL DATA

| | |
|-----------------------------------|----------|
| Voltage (type): | DC |
| Voltage Interval (V): | 12...12V |
| Voltage Nominal (V): | 12 |
| Voltage Forward (Vf): | 9 |
| Max. Power Luminaire (W): | 0,8 |
| Max. System Power (W): | 0,8 |
| Max. Efficiency Luminaire (lm/W): | 3,8 |
| Max. Efficiency System (lm/W): | 3,8 |

OPERATION AND CONNECTION

| | |
|-------------------------|-------------------------|
| Dimmable: | No |
| Type of Dimming: | OnOff |
| Driver Included: | No |
| Driver Model: | Constant Voltage |
| Connection (type): | Screw Connection, Cable |
| Length Connection (cm): | 50 |
| Connection (mm2): | 2x0,5 |
| Through Wiring: | Yes |
| Min. Ta (°C): | -25 |
| Max. Ta (°C): | 45 |
| Max. Tc (°C): | 80 |

COLOR AND MATERIAL

| | |
|-----------|-----------|
| Material: | Aluminium |
| Color: | Aluminum |

MEASUREMENT AND INSTALLATION

| | |
|----------------------------|----------------|
| Operating Environment: | Outdoor |
| IP Degree of Protection: | 67 |
| Protection Class: | III |
| Installation: | Built-in |
| Mounting Installation: | Tension Spring |
| Max. Pressure (kg): | 100 |
| Approval Marks: | CE |
| Height (mm): | 34 |
| Diameter (mm): | 36 |
| Weight (kg): | 0,07 |
| Min. Built-in (mm): | Ø28x25 |
| Height Recessed Part (mm): | 23 |
| Height Exterior Part (mm): | 13 |
| Built-in Ø (mm): | 28mm |



