



## STEPLIGHT GARDEN KIT

Kit for decorative step lighting with low energy consumption. Create striking staircase lighting, for example on patios and decks. The kit includes 4x IP67 luminaires, 3x 1m extension cables with quick connectors and 1x IP44 plug-in transformer with 5m cable. Can be combined with Spotlight Garden and Decklight Garden thanks to the common coupling system. Up to 12 luminaires can be connected to a single transformer.

### DESCRIPTION

<b>GTIN:</b>	7392971133157
<b>Item Name:</b>	Steplight Garden Kit
<b>Warranty:</b>	5 years
<b>Type:</b>	.

### LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	3
<b>Light Source:</b>	LED
<b>Light Source Included:</b>	Yes
<b>Replaceability:</b>	Non-replaceable LED, Replaceable Control gear by end-user
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>80
<b>Colour Consistency (SDCM):</b>	3
<b>Light sharing:</b>	Asymmetric
<b>Light Outlet:</b>	Direct
<b>Number of Lamps (pcs):</b>	4
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	h Ta °C
<b>Nominal Life Time (h):</b>	50000
<b>Lumen maintenance 50 000h:</b>	L70
<b>LLMF @ 50 000h:</b>	0.7
<b>Life Time Driver:</b>	50 000h/10%

## TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50
Voltage Forward (Vf):	9
Max. Power Luminaire (W):	0,8
Max. System Power (W):	4,5
Max. Efficiency System (lm/W):	1

## OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	OnOff
Driver Included:	Yes
Driver Model:	Constant Voltage
Driver Type:	Stand Alone
Connection (type):	Screw Connection, Cable
Length Connection (cm):	50
Connection (mm <sup>2</sup> ):	2x0,5
Through Wiring:	Yes
Min. Ta (°C):	-25
Max. Ta (°C):	45
Max. Tc (°C):	80

## COLOR AND MATERIAL

Material:	Aluminium
Color:	Aluminum

## MEASUREMENT AND INSTALLATION

Operating Environment:	Outdoor
IP Degree of Protection:	67
Protection Class:	III
Installation:	Built-in
Mounting Installation:	Tension Spring
Max. Pressure (kg):	100
Approval Marks:	CE
Height (mm):	34
Diameter (mm):	36
Weight (kg):	0,71
Min. Built-in (mm):	Ø28x25
Height Recessed Part (mm):	23
Height Exterior Part (mm):	13
Built-in Ø (mm):	28mm

