



## DECKLIGHT SUPER GARDEN KIT

Kit with accent luminaire in IP67 for e.g. wooden decks, stone walls and embedment. Use clips for optimal grip even in living materials, such as wood. Supplied with 2 0.5m rubber cables with screw connections and transformers in IP44 placed above ground. The kit includes 2pcs IP67 luminaires, 1pc 1m extension cable with quick connection and 1 Trafo Garden 12W with 5m cable. Can be combined with all luminaires in the Garden family thanks to the common connection system.

### DESCRIPTION

<b>GTIN:</b>	7392971135038
<b>Item Name:</b>	Decklight Super Garden Kit
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	75
<b>Light Source:</b>	LED
<b>Light Source Included:</b>	Yes
<b>Replaceability:</b>	Non-replaceable LED, Replaceable Control gear by end-user
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>90
<b>Colour Consistency (SDCM):</b>	3
<b>Luminous Intensity (cd):</b>	2x115
<b>Beam Angle (°):</b>	45
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Direct
<b>Number of Lamps (pcs):</b>	2
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	h Ta °C
<b>Nominal Life Time (h):</b>	100000
<b>Lumen maintenance 100 000h:</b>	L70
<b>LLMF @ 100 000h:</b>	0.7
<b>Life Time Driver:</b>	50 000h/10%

## TECHNICAL DATA

Voltage (type):	DC
Voltage Interval (V):	12...12V
Voltage Nominal (V):	12
Line Frequency (Hz):	50
Voltage Forward (Vf):	9
Max. Power Luminaire (W):	1,1
Max. System Power (W):	2,75
Max. Efficiency Luminaire (lm/W):	75
Max. Efficiency System (lm/W):	38

Containing light source energy efficiency class (EU) 2019/2015: G

## OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	OnOff
Driver Included:	Yes
Driver Model:	Constant Voltage
Driver Type:	Stand Alone
Connection (type):	Plug-in, Quick Connection
Length Connection (cm):	50
Connection (mm <sup>2</sup> ):	2x0,5
Through Wiring:	Yes
Strain Relief:	Yes
Min. Ta (°C):	-25
Max. Ta (°C):	45
Max. Tc (°C):	80

## COLOR AND MATERIAL

Material:	Aluminium
Color:	Aluminum

## MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	67
Protection Class:	III
Installation:	Built-in
Mounting Installation:	Tension Spring, Mounting Sleeve
Max. Pressure (kg):	100
Approval Marks:	CE
Impact Strength:	IK08
Filament Test IEC 695-2-1(°C):	650
Height (mm):	63
Diameter (mm):	42
Weight (kg):	0,4634
Min. Built-in (mm):	Ø30x71
Height Recessed Part (mm):	60
Height Exterior Part (mm):	3
Built-in Ø (mm):	34mm

