



## CONVERTER DALI 180MA

DALI converter for constant current luminaires. The primary side has push-in, loop-in, loop-out terminals and screwless strain relief for cables. Secondary side has prepared wires with phono connectors.

### DESCRIPTION

<b>GTIN:</b>	7392971130170
<b>Item Name:</b>	Converter DALI 180mA
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Life Time Driver:</b>	50 000h/10%
--------------------------	-------------

### TECHNICAL DATA

<b>Voltage (type):</b>	AC
<b>Voltage Interval (V):</b>	220...240V
<b>Voltage Nominal (V):</b>	230
<b>Line Frequency (Hz):</b>	50

## OPERATION AND CONNECTION

<b>Dimmable:</b>	Yes
<b>Type of Dimming:</b>	Push 230V, DALI 2
<b>Driver Model:</b>	Constant Current
<b>Driver Type:</b>	Stand Alone
<b>Connection (type):</b>	Quick Terminal
<b>Connection (mm2):</b>	4x0,5-2,5
<b>Through Wiring:</b>	Yes
<b>Strain Relief:</b>	Yes
<b>Connection Secondary (type):</b>	Cable
<b>Length Connection Secondary (cm):</b>	30
<b>Secondary Outputs (pair):</b>	1
<b>Voltage Output Interval (V):</b>	32-39V
<b>Efficiency (%):</b>	75
<b>Power Interval for Catalogue (W):</b>	5,8-7
<b>Max. Power (W):</b>	7
<b>Standby Power:</b>	1
<b>Constant Current (mA):</b>	180
<b>Min. Ta (°C):</b>	-20
<b>Max. Ta (°C):</b>	45
<b>Max. Tc (°C):</b>	85
<b>Dimming secondary side:</b>	AM
<b>Protection Against:</b>	Short Circuit, Overload, Overheating 100°C

## COLOR AND MATERIAL

<b>Material:</b>	Plastic
<b>Color:</b>	White

## MEASUREMENT AND INSTALLATION

<b>Operating Environment:</b>	Indoor / dry locations
<b>IP Degree of Protection:</b>	20
<b>Protection Class:</b>	II
<b>Installation:</b>	Surface mounted
<b>Fire Safety Marks:</b>	MM-mark
<b>Approval Marks:</b>	CE
<b>Length (mm):</b>	122
<b>Width (mm):</b>	56
<b>Height (mm):</b>	30
<b>Weight (kg):</b>	0,117
<b>Built-in Ø (mm):</b>	73mm

