



CONVERTER DALI 180MA

DALI converter for constant current luminaires. The primary side has push-in, loop-in, loop-out terminals and screwless strain relief for cables. Secondary side has prepared wires with phono connectors.

DESCRIPTION

GTIN:	7392971130170
Item Name:	Converter DALI 180mA
Warranty:	5 years

LIGHT TECHNICAL DATA

Life Time Driver:	50 000h/10%
--------------------------	-------------

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Push 230V, DALI 2
Driver Model:	Constant Current
Driver Type:	Stand Alone
Connection (type):	Quick Terminal
Connection (mm²):	4x0,5-2,5
Through Wiring:	Yes
Strain Relief:	Yes
Connection Secondary (type):	Cable
Length Connection Secondary (cm):	30
Secondary Outputs (pair):	1
Voltage Output Interval (V):	32-39V
Efficiency (%):	75
Power Interval for Catalogue (W):	5,8-7
Standby Power:	1
Constant Current (mA):	180
Min. Ta (°C):	-20
Max. Ta (°C):	45
Max. Tc (°C):	85
Dimming secondary side:	AM
Protection Against:	Short Circuit, Overload, Overheating 100°C

COLOR AND MATERIAL

Material:	Plastic
Color:	White

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Surface mounted
Fire Safety Marks:	MM-mark
Approval Marks:	CE
Length (mm):	122
Width (mm):	56
Height (mm):	30
Weight (kg):	0,117
Built-in Ø (mm):	73mm



(mm)

