



CONVERTER MINI MD FDIM 700MA

Mains dimmable converter for constant current that can be regulated with normal standard rotating/press dimmers for leading-edge and trailing-edge control. Slim design for installation in 1 ½ box or together with the luminaire in Spot Guard Gles. Push-in terminal blocks with room for through wiring on the primary side for simple installation.

DESCRIPTION

GTIN:	7392971126616
Item Name:	Converter Mini MD FDIM 700mA
Warranty:	5 years

LIGHT TECHNICAL DATA

Life Time Driver:	50 000h/5%
Flicker (PstLM):	0,037
Stroboscopic effect (SVM):	0,026

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Trailing Edge, Leading Edge
Driver Model:	Constant Current
Driver Type:	Stand Alone
Connection (type):	Quick Terminal
Connection (mm2):	4x0,5-1,5
Through Wiring:	Yes
Strain Relief:	Yes
Connection Secondary (type):	Quick Terminal
Secondary Connection (mm2):	2x0,5-1,5
Secondary Outputs (pair):	1
Voltage Output Interval (V):	8-28V
Power Interval for Catalogue (W):	6-20
Constant Current (mA):	700
Current (A):	0,11
Min. Ta (°C):	-25
Max. Ta (°C):	45
Max. Tc (°C):	75
Protection Against:	Short Circuit, Overload, Overheating 110°C

COLOR AND MATERIAL

Material:	Plastic
Color:	White

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Built-in, Surface mounted
Mounting Installation:	Screw Mounting
Fire Safety Marks:	MM-mark
Approval Marks:	CE
Length (mm):	111
Width (mm):	52
Height (mm):	22
Weight (kg):	0,105
Built-in Ø (mm):	55mm

