



## CONVERTER MICRO MD FDIM 350MA

Mains dimmable converter for constant current that can be regulated with normal standard rotating/press dimmers for leading-edge and trailing-edge control. Slim design for installation in appliance box with extra space or together with the luminaire in Spot Guard Gles.

### DESCRIPTION

<b>GTIN:</b>	7392971127507
<b>Item Name:</b>	Converter Micro MD FDIM 350mA
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Life Time Driver:</b>	50 000h/5%
<b>Flicker (PstLM):</b>	0,037
<b>Stroboscopic effect (SVM):</b>	0,026

### OPERATION AND CONNECTION

<b>Dimmable:</b>	Yes
<b>Type of Dimming:</b>	Trailing Edge, Leading Edge
<b>Driver Model:</b>	Constant Current
<b>Driver Type:</b>	Stand Alone
<b>Connection (type):</b>	Screw Terminals
<b>Connection (mm2):</b>	2x0,5-2,5
<b>Strain Relief:</b>	Yes
<b>Connection Secondary (type):</b>	Screw Terminals
<b>Secondary Connection (mm2):</b>	2x0,5-2,5
<b>Secondary Outputs (pair):</b>	1
<b>Voltage Output Interval (V):</b>	12-28V
<b>Power Interval for Catalogue (W):</b>	4,2-10
<b>Max. Power (W):</b>	10
<b>Constant Current (mA):</b>	350
<b>Current (A):</b>	0,06
<b>Min. Ta (°C):</b>	-25
<b>Max. Ta (°C):</b>	45
<b>Max. Tc (°C):</b>	70
<b>Protection Against:</b>	Short Circuit, Overload, Overheating 110°C

## COLOR AND MATERIAL

Material:	Plastic
Color:	White

## MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Built-in, Surface mounted
Mounting Installation:	Screw Mounting
Fire Safety Marks:	MM-mark
Approval Marks:	CE
Length (mm):	102
Width (mm):	37
Height (mm):	21
Weight (kg):	0,065
Built-in Ø (mm):	46mm

