



CONVERTER ROUND DALI/PUSH 350/700MA 9W

Small and versatile dimmable LED converter for constant current 350/700mA with easy setting of current via dip switch Suitable for junction box, which makes it easy to place. Excellent for smaller constant current luminaires, such as lighting in window niches. Dimmable via Push (230V) or DALI. Converter Round has memory function which lights up with latest set value after power failure. For further technical information see instruction manual.

DESCRIPTION

GTIN:	7392971136653
Item Name:	Converter Round DALI/PUSH 350/700mA 9W
Warranty:	5 years

LIGHT TECHNICAL DATA

Life Time Driver:	50 000h/15%
--------------------------	-------------

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	180...260V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Push 230V, DALI 2, DALI DT6
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Cable
Length Connection (cm):	10
Connection (mm²):	2x0,75
Connection Secondary (type):	Cable
Length Connection Secondary (cm):	10
Secondary Connection (mm²):	2x0,75
Voltage Output Interval (V):	3-26V
Power Factor λ:	0,9
Efficiency (%):	80
Power Interval for Catalogue (W):	1-9
Max. Power (W):	9
Standby Power:	1
Constant Current (mA):	350, 700
Min. Ta (°C):	-20
Max. Ta (°C):	45
Max. Tc (°C):	85
Dimming secondary side:	PWM
Frequency PWM dimming (Hz):	>300
Memory Function Power Failure:	Yes
Protection Against:	Short Circuit, Overheating 110°C, Overload
Fuse B10 (pcs):	70
Fuse B16 (pcs):	110
Fuse C10 (pcs):	80
Fuse C16 (pcs):	220

COLOR AND MATERIAL

Material:	Plastic
Color:	White
Environmental Assessment:	Byggvarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Built-in
Fire Safety Marks:	MM-mark
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Height (mm):	24
Diameter (mm):	57
Weight (kg):	0,1
Built-in Ø (mm):	58mm



(mm)

