



## CONVERTER FDIM G3 180MA

Mains dimmable driver for constant current luminaire 180mA. Push-in, loop-in, loop-out terminals for through wiring and screwless strain relief for cables from 0.5-2.5mm<sup>2</sup> on primary side, for cable/16mm flex hose. The secondary side has pre-wired cable and phono connector.

### DESCRIPTION

<b>GTIN:</b>	7392971136349
<b>Item Name:</b>	Converter FDIM G3 180mA
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Life Time Driver:</b>	50 000h/10%
--------------------------	-------------

### OPERATION AND CONNECTION

<b>Dimmable:</b>	Yes
<b>Type of Dimming:</b>	Trailing Edge, Leading Edge
<b>Driver Model:</b>	Constant Current
<b>Driver Type:</b>	Stand Alone
<b>Connection (type):</b>	Quick Terminal
<b>Through Wiring:</b>	Yes
<b>Strain Relief:</b>	Yes
<b>Power Interval for Catalogue (W):</b>	1-7,5
<b>Constant Current (mA):</b>	180
<b>Min. Ta (°C):</b>	-20
<b>Max. Ta (°C):</b>	45
<b>Max. Tc (°C):</b>	75
<b>Protection Against:</b>	Short Circuit

### COLOR AND MATERIAL

<b>Material:</b>	Plastic
<b>Color:</b>	White

## MEASUREMENT AND INSTALLATION

<b>Operating Environment:</b>	Indoor / dry locations
<b>IP Degree of Protection:</b>	20
<b>Protection Class:</b>	II
<b>Installation:</b>	Surface mounted
<b>Fire Safety Marks:</b>	Not in insulation without protection cover
<b>Approval Marks:</b>	CE
<b>Length (mm):</b>	99
<b>Width (mm):</b>	45
<b>Height (mm):</b>	26
<b>Weight (kg):</b>	0,113

