



SLD FDIM 12V 75W

Mains dimmable driver for LED trafo. The light can be regulated using common standard rotary/push-button dimmers for leading-edge and trailing-edge control. Protection against short circuiting, overloading and overheating with automatic restart.

DESCRIPTION

GTIN:	7392971130194
Item Name:	SLD FDIM 12V 75W
Warranty:	5 years

LIGHT TECHNICAL DATA

Life Time Driver:	50 000h/5%
-------------------	------------

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Trailing Edge, Leading Edge
Driver Model:	Constant Voltage
Driver Type:	Stand Alone
Connection (type):	Screw Terminals
Connection (mm2):	2x0,5-1,5
Strain Relief:	Yes
Connection Secondary (type):	Screw Terminals
Secondary Connection (mm2):	2x0,5-1,5
Secondary Outputs (pair):	1
Power Factor λ :	0,95
Power Interval for Catalogue (W):	12-75
Max. Power (W):	75
Min. Ta (°C):	-20
Max. Ta (°C):	45
Max. Tc (°C):	80
Protection Against:	Short Circuit, Overload, Overheating 110°C
Fuse B10 (pcs):	8
Fuse B16 (pcs):	14
Fuse C10 (pcs):	14
Fuse C16 (pcs):	23

COLOR AND MATERIAL

Material:	Plastic
Color:	White

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Length (mm):	185
Width (mm):	60
Height (mm):	31
Weight (kg):	0,43
Built-in Ø (mm):	70mm

