



## LED-DRIVER VSTR 24VDC 120W

### DESCRIPTION

|            |                            |
|------------|----------------------------|
| GTIN:      | 7392971123639              |
| Item Name: | LED-driver VSTR 24VDC 120W |
| Warranty:  | 5 years                    |

### LIGHT TECHNICAL DATA

|                            |       |
|----------------------------|-------|
| Flicker (PstLM):           | 0,101 |
| Stroboscopic effect (SVM): | 0,009 |

### TECHNICAL DATA

|                       |            |
|-----------------------|------------|
| Voltage (type):       | AC         |
| Voltage Interval (V): | 220...240V |
| Voltage Nominal (V):  | 230        |
| Line Frequency (Hz):  | 50         |

## OPERATION AND CONNECTION

|  |  |
|--|--|
| <b>Dimmable:</b>                         | Yes  |
| <b>Type of Dimming:</b>                  | Push 230V, 1-10V, DMX                      |
| <b>Driver Model:</b>                     | Constant Voltage                           |
| <b>Driver Type:</b>                      | Stand Alone                                |
| <b>Connection (type):</b>                | Quick Terminal                             |
| <b>Connection (mm2):</b>                 | 3x0,5-2,5                                  |
| <b>Strain Relief:</b>                    | Yes  |
| <b>Connection Secondary (type):</b>      | Quick Terminal                             |
| <b>Secondary Connection (mm2):</b>       | 4x0,5-2,5                                  |
| <b>Secondary Outputs (pair):</b>         | 3  |
| <b>Power Interval for Catalogue (W):</b> | 0-120                                      |
| <b>Max. Power (W):</b>                   | 120  |
| <b>Max. Load Per Output (W):</b>         | 100  |
| <b>Min. Ta (°C):</b>                     | -25  |
| <b>Max. Ta (°C):</b>                     | 50   |
| <b>Max. Tc (°C):</b>                     | 75   |
| <b>Memory Function Power Failure:</b>    | Yes  |
| <b>Protection Against:</b>               | Short Circuit, Overload, Overheating 100°C |
| <b>Fuse B10 (pcs):</b>                   | 5  |
| <b>Fuse B16 (pcs):</b>                   | 8  |
| <b>Fuse C10 (pcs):</b>                   | 8  |
| <b>Fuse C16 (pcs):</b>                   | 13   |

## COLOR AND MATERIAL

|                                  |                     |
|----------------------------------|---------------------|
| <b>Color:</b>                    | White               |
| <b>Environmental Assessment:</b> | Byggvarubedömningen |

## MEASUREMENT AND INSTALLATION

|                                 |                        |
|---------------------------------|------------------------|
| <b>Operating Environment:</b>   | Indoor / dry locations |
| <b>IP Degree of Protection:</b> | 20                     |
| <b>Protection Class:</b>        | I                      |
| <b>Installation:</b>            | Surface mounted        |
| <b>Fire Safety Marks:</b>       | MM-mark                |
| <b>Approval Marks:</b>          | CE                     |
| <b>Length (mm):</b>             | 240                    |
| <b>Width (mm):</b>              | 60                     |
| <b>Height (mm):</b>             | 49                     |
| <b>Weight (kg):</b>             | 0,32                   |
| <b>Built-in Ø (mm):</b>         | 80mm                   |



