



LED-DIMTRAFO MDR DALI 24V 100W

Sturdy dimmer trafo for 24V LED light source, all-in-one function (trafo with integrated PWM dimmer). Dimming via DALI, potential-free pushbutton, potentiometer or 1-10V. Optional memory function (lights up with latest set value) after power failure, also via pushbutton. 1-10 units can be linked together and controlled from one or more locations with a spring-loaded potential-free pushbutton. Two outputs with push-in terminals, the entire capacity can be taken out via one output or split.

DESCRIPTION

GTIN:	7392971127804
Item Name:	LED-dimtrafo MDR DALI 24V 100W
Warranty:	5 years

LIGHT TECHNICAL DATA

Life Time Driver:	40 000h/8%
--------------------------	------------

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Push 230V, Push 24V, 0-10V, 1-10V, Potentiometer, DALI 2
Driver Model:	Constant Voltage
Driver Type:	Stand Alone
Connection (type):	Quick Terminal
Strain Relief:	Yes
Connection Secondary (type):	Quick Terminal
Secondary Connection (mm2):	2x0,5-2,5
Power Interval for Catalogue (W):	10-100
Max. Power (W):	100
Min. Ta (°C):	-10
Max. Ta (°C):	40
Max. Tc (°C):	70
Memory Function Power Failure:	Yes
Protection Against:	Short Circuit, Overload, Overheating 110°C
Fuse B10 (pcs):	8
Fuse B16 (pcs):	13
Fuse C10 (pcs):	12
Fuse C16 (pcs):	20

COLOR AND MATERIAL

Material:	Plastic
Color:	White
Environmental Assessment:	Byggvarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Fire Safety Marks:	MM-mark
Approval Marks:	CE
Length (mm):	207
Width (mm):	76
Height (mm):	35
Weight (kg):	0,35
Built-in Ø (mm):	85mm

