



LED-DIMTRAFO RGB DALI 24V 120W

Powerful dimmer trafo for 24V LED strips RGBW/TW Perfect for dimming and colour control via DALI2 with only one address (type DT8). Memory function which lights up with latest set value after power failure.

DESCRIPTION

GTIN:	7392971136776
Item Name:	LED-dimtrafo RGB DALI 24V 120W
Warranty:	5 years

LIGHT TECHNICAL DATA

Life Time Driver:	50 000h/15%
-------------------	-------------

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	180...260V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Push 230V, DALI 2, DALI DT8
Driver Model:	Constant Voltage
Driver Type:	Stand Alone
Connection (type):	Screw Terminals
Connection (mm²):	2x0,5-2,5
Strain Relief:	Yes
Connection Secondary (type):	Quick Terminal
Secondary Connection (mm²):	2x0,5-2,5
Secondary Outputs (pair):	4
Power Factor λ:	0,95
Efficiency (%):	90
Power Interval for Catalogue (W):	1-120
Max. Power (W):	120
Standby Power:	1
Max. Load Per Output (W):	120
Current (A):	5
Min. Ta (°C):	-25
Max. Ta (°C):	45
Max. Tc (°C):	85
Dimming secondary side:	PWM
Frequency PWM dimming (Hz):	>300
Memory Function Power Failure:	Yes
Protection Against:	Overheating 110°C, Overload
Fuse B10 (pcs):	13
Fuse B16 (pcs):	20
Fuse C10 (pcs):	14
Fuse C16 (pcs):	22

COLOR AND MATERIAL

Material:	Plastic
Color:	White
Environmental Assessment:	Byggvarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Fire Safety Marks:	MM-mark
Approval Marks:	CE, ENEC 25
Filament Test IEC 695-2-1(°C):	650
Length (mm):	244
Width (mm):	64
Height (mm):	32
Weight (kg):	0,5
Built-in Ø (mm):	70mm

