hidealite | Elektro Elco AB Tallvägen 5, 564 35 Bankeryd, Sweden
Phone + 46(0)36 290 60 00 | info@elco.se | www.hidealite.com





CONVERTER MICRO MD FDIM 700MA

Mains dimmable converter for constant current that can be regulated with normal standard rotating/press dimmers for leading-edge and trailing-edge control. Slim design for installation in appliance box with extra space or together with the luminaire in Spot Guard Gles.

DESCRIPTION

GTIN:	7392971127514
Item Name:	Converter Micro MD FDIM 700mA
Warranty:	5 years

LIGHT TECHNICAL DATA

Life Time Driver:	50 000h/5%
Flicker (PstLM):	0,037
Stroboscopic effect (SVM):	0,026

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Trailing Edge, Leading Edge
Driver Model:	Constant Current
Driver Type:	Stand Alone
Connection (type):	Screw Terminals
Connection (mm2):	2x0,5-2,5
Strain Relief:	Yes
Connection Secondary (type):	Screw Terminals
Secondary Connection (mm2):	2x0,5-2,5
Secondary Outputs (pair):	1
Voltage Output Interval (V):	6-14V
Power Interval for Catalogue (W):	4,2-10
Max. Power (W):	10
Constant Current (mA):	700
Current (A):	0,06
Operating Temperature:	-25...+45°C
Max. Tc (°C):	70
Protection Against:	Short Circuit, Overload, Overheating 110°C

COLOR AND MATERIAL

Material:	Plastic
Color:	White

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Built-in, Surface mounted
Mounting Installation:	Screw Mounting
Fire Safety Marks:	MM-mark
Approval Marks:	CE
Length (mm):	102
Width (mm):	37
Height (mm):	21
Weight (kg):	0,065
Built-in Ø (mm):	46mm



