hidealite | Elektro Elco AB Tallvägen 5, 564 35 Bankeryd, Sweden
Phone + 46(0)36 290 60 00 | info@elco.se | www.hidealite.com





MILO G2 S WHITE

Description

Milo G2 is a dimmable facade light with a timeless design that provides an even and pleasant light pattern on wall and ground. Available with up and downlight or downlight only. Equally suitable for entrances, along facades, or garages – in both private and public environments.

Light Technical Data

Built-in DIP switch (3000K/4000K) for color temperature adjustment (M-XXL). Reflector technology. Available with LED or GU10. Ra>90.

Technical data

Built-in DIP switch for luminous flux adjustment, M-XXL, not S or DALI-2. Replaceable LED and driver for easy servicing. Dimmable via phase dimming (S-XXL) or DALI-2 (XXL). LED lifetime: L80 100 000h Ta25°C. Driver lifetime: 50 000h /5%.

Color and material

Available in white, grey, black, or galvanized steel, C4. The galvanized version develops a natural patina over time.

Measurement and installation

IP65, and galv IP44. The backplate mounts easily to the wall with double grommets (M-XXL) for feed-through wiring. Prepared for surface-mounted cabling (M-XXL). Spacers for surface cabling included (S). Luminaire easily hangs in place afterwards.

DESCRIPTION

GTIN:	7392971155593
Item Name:	Milo G2 S White
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	340
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Replaceable LED by professional, Replaceable Control gear by professional
LED Colour:	Warm White
Colour Temperature (K):	3000
Colour Rendering Index (Ra):	>90
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	930
Beam Angle (°):	30
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	L80 100 000h Ta 25°C
Nominel Life Time (h):	100000
Lumen maintenance 50 000h:	L92
Lumen maintenance 75 000h:	L89
Lumen maintenance 100 000h:	L86
LLMF @ 50 000h:	0.92
LLMF @ 100 000h:	0.86
Life Time Driver:	50 000h/5%
Flicker (PstLM):	1
Stroboscopic effect (SVM):	0,4

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	60, 50
Power LED (W):	3,1
Max. Power Luminaire (W):	4,5
Max. System Power (W):	4,5
Max. Efficiency Luminaire (lm/W):	75,6
Max. Efficiency System (lm/W):	75,6
Containing light source energy efficiency class (EU) 2019/2015:	E
Eprel registration number:	2336591

OPERATION AND CONNECTION


Dimmable:	Yes
Type of Dimming:	Trailing Edge
Driver Included:	Yes - replaceable
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm2):	3x0,75-2,5
Through Wiring:	No
Strain Relief:	Yes
Power Factor λ:	0,9
Efficiency (%):	68
Power loss (W):	1,5
Leakage current (mA) (at 230 V, 50 Hz, full load):	5
THD (%):	25
Constant Current (mA):	350
Operating Temperature:	-20...+45°C
Max. Tc (°C):	85
Mains surge protection DM (kV):	1,5
Mains surge protection CM (kV):	2
Fuse B10 (pcs):	140
Fuse B16 (pcs):	224
Fuse C10 (pcs):	250
Fuse C16 (pcs):	400


COLOR AND MATERIAL

Material:	Aluminium
Color:	White
Environmental Assessment:	EPD
Available in special color:	No


MEASUREMENT AND INSTALLATION

Operating Environment:	Outdoor, Indoor / wet locations, Indoor / damp locations, Indoor / dry locations
IP Degree of Protection:	65
Protection Class:	I
Installation:	Wall
Mounting Installation:	Screw Mounting
Approval Marks:	a Hide-a-lite Choice
Impact Strength:	IK06
Filament Test IEC 695-2-1(°C):	650
Length (mm):	116
Width (mm):	58
Height (mm):	78
Diameter (mm):	58
Weight (kg):	0,44








(mm)
78
55
96
116
Ø58
31