



SCOUT G2 XL 4000K ASYM

Robust floodlight in five sizes - perfectly suited for outdoor environments such as warehouse doors or as parking, facade or signage lighting. Scout G2 offers many possibilities, with accessories in various combinations to suit different areas of application. Accessories are supplied with bolts, nuts and screws to permit various combinations. Asymmetric light distribution and high luminous efficacy. Adjustable bracket, fitted with screws. With Scout G2 XS, you can easily change the output with DIP-Switch Power. Comes complete with integrated and replaceable driver and 2m rubber cable for direct 230V connection.

DESCRIPTION

GTIN:	7392971146140
Item Name:	Scout G2 XL 4000K Asym
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	28000
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Non-replaceable LED, Replaceable Control gear by professional
LED Colour:	White
Colour Temperature (K):	4000
Colour Rendering Index (Ra):	>80
Colour Consistency (SDCM):	5
Luminous Intensity (cd):	8750
Beam Angle (°):	150
Light sharing:	Asymmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	240
Life Time:	h Ta °C
Nominal Life Time (h):	100000
Lumen maintenance 50 000h:	L87
Lumen maintenance 75 000h:	L80
Lumen maintenance 100 000h:	L74
LLMF @ 50 000h:	0.87
LLMF @ 100 000h:	0.74
Life Time Driver:	50 000h/5%
Flicker (PstLM):	0,01
Stroboscopic effect (SVM):	0,0026

TECHNICAL DATA

Adjustable:	Yes
Tiltable (°):	270
Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50
Power LED (W):	186
Max. Power Luminaire (W):	200
Max. System Power (W):	200
Max. Efficiency Luminaire (lm/W):	140
Max. Efficiency System (lm/W):	140
Containing light source energy efficiency class (EU) 2019/2015: E	

OPERATION AND CONNECTION

Dimmable:	No
Driver Included:	Yes
Driver Model:	Constant Voltage
Driver Type:	Built-in
Connection (type):	Cable
Length Connection (cm):	200
Connection (mm ²):	3x1,0
Through Wiring:	No
Strain Relief:	Yes
Power Factor λ :	0,9
Efficiency (%):	90
Power loss (W):	14
Leakage current (mA) (at 230 V, 50 Hz, full load):	5
THD (%):	20
Constant Current (mA):	780
Min. Ta (°C):	-30
Max. Ta (°C):	50
Max. Tc (°C):	105
Inrush current (max/time):	80A 350 μ s
Mains surge protection DM (kV):	4
Mains surge protection CM (kV):	6
Fuse B10 (pcs):	6
Fuse B16 (pcs):	9
Fuse C10 (pcs):	7
Fuse C16 (pcs):	11

COLOR AND MATERIAL

Material:	Aluminium
Color:	Black
Environmental Assessment:	Byggvarubedömningen
Available in special color:	No

MEASUREMENT AND INSTALLATION

Operating Environment:	Outdoor
IP Degree of Protection:	66
Protection Class:	I
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Fire Safety Marks:	D-mark
Approval Marks:	CE
Impact Strength:	IK08
Filament Test IEC 695-2-1(°C):	850
Length (mm):	446
Width (mm):	345
Height (mm):	62
Weight (kg):	5,043



