



## CASE WALL IP55 ANTHRACITE

Trendy wall-mounted luminaire for outdoor use with a light pattern that illuminates 145° both up and down. This luminaire comprises an aluminium frame and is fitted with an LED-Multichip of 6W. Perfect for installing on facades, for example entrances or patios in private and public areas. The luminaire is anodised and powder-coated for harsh outdoor climates. Integrated driver. For installation on walls with a concealed connector.

### DESCRIPTION

<b>GTIN:</b>	7392971131672
<b>Item Name:</b>	Case Wall IP55 Anthracite
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	500
<b>Light Source:</b>	LED
<b>Light Source Included:</b>	Yes
<b>Replaceability:</b>	Non-replaceable LED, Replaceable Control gear by professional
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>80
<b>Colour Consistency (SDCM):</b>	3
<b>Beam Angle (°):</b>	145
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Indirect
<b>Number of Lamps (pcs):</b>	1
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	h Ta °C
<b>Nominal Life Time (h):</b>	50000
<b>Life Time Driver:</b>	50 000h/10%
<b>Flicker (PstLM):</b>	0,05
<b>Stroboscopic effect (SVM):</b>	0

## TECHNICAL DATA

<b>Voltage (type):</b>	AC
<b>Voltage Interval (V):</b>	230...230V
<b>Voltage Nominal (V):</b>	230
<b>Max. Power Luminaire (W):</b>	9
<b>Max. Efficiency Luminaire (lm/W):</b>	56
<b>Containing light source energy efficiency class (EU) 2019/2015: E</b>	

## OPERATION AND CONNECTION

<b>Dimmable:</b>	No
<b>Type of Dimming:</b>	OnOff
<b>Driver Included:</b>	Yes
<b>Driver Model:</b>	Constant Current
<b>Driver Type:</b>	Built-in
<b>Connection (type):</b>	Screw Terminals
<b>Min. Ta (°C):</b>	-20
<b>Max. Ta (°C):</b>	35
<b>Fuse B10 (pcs):</b>	46
<b>Fuse B16 (pcs):</b>	74
<b>Fuse C10 (pcs):</b>	93
<b>Fuse C16 (pcs):</b>	149

## COLOR AND MATERIAL

<b>Material:</b>	Aluminium
<b>Color:</b>	Antracit
<b>Environmental Assessment:</b>	Byggvarubedömningen

## MEASUREMENT AND INSTALLATION

<b>Operating Environment:</b>	Indoor / wet locations, Outdoor
<b>IP Degree of Protection:</b>	55
<b>Protection Class:</b>	I
<b>Installation:</b>	Surface mounted
<b>Mounting Installation:</b>	Screw Mounting
<b>Approval Marks:</b>	CE
<b>Impact Strength:</b>	IK04
<b>Length (mm):</b>	130
<b>Width (mm):</b>	130
<b>Height (mm):</b>	80
<b>Weight (kg):</b>	1



