



## CASE WALL IP55 ANTHRACITE

Trendy wall-mounted luminaire for outdoor use with a light pattern that illuminates 145° both up and down. This luminaire comprises an aluminium frame and is fitted with an LED-Multichip of 6W. Perfect for installing on facades, for example entrances or patios in private and public areas. The luminaire is anodised and powder-coated for harsh outdoor climates. Integrated driver. For installation on walls with a concealed connector.

### DESCRIPTION

<b>GTIN:</b>	7392971131672
<b>Item Name:</b>	Case Wall IP55 Anthracite
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	500
<b>Light Source:</b>	LED
<b>Light Source Included:</b>	Yes
<b>Replaceability:</b>	Non-replaceable LED, Replaceable Control gear by professional
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>80
<b>Colour Consistency (SDCM):</b>	3
<b>Beam Angle (°):</b>	145
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Indirect
<b>Number of Lamps (pcs):</b>	1
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	L70 50000h Ta 25°C
<b>Nominal Life Time (h):</b>	50000
<b>Life Time Driver:</b>	50 000h/10%
<b>Flicker (PstLM):</b>	0,05
<b>Stroboscopic effect (SVM):</b>	0

## TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	230...230V
Voltage Nominal (V):	230
Max. Power Luminaire (W):	9
Max. Efficiency Luminaire (lm/W):	55,6
Containing light source energy efficiency class (EU) 2019/2015: E	

## OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	OnOff
Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Screw Terminals
Min. Ta (°C):	-20
Max. Ta (°C):	35
Fuse B10 (pcs):	46
Fuse B16 (pcs):	74
Fuse C10 (pcs):	93
Fuse C16 (pcs):	149

## COLOR AND MATERIAL

Material:	Aluminium
Color:	Antracit
Environmental Assessment:	Byggvarubedömningen

## MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	55
Protection Class:	I
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK04
Length (mm):	130
Width (mm):	130
Height (mm):	80
Weight (kg):	1



