



MILO XL I ANTHRACITE 3000K

Wall-mounted luminaire with timeless design with downward light emission. LED COB with reflector optics and well-conceived design provides a good light spread and good luminous comfort. Separate rear element with dual cable bushings and push-in, loop-in, loop-out terminal block for easy installation. IP55 design with anodised and powder-coated housing for rough outdoor climate. Comes with built-in driver and spacers for surface-mounted cable routing.

DESCRIPTION

GTIN:	7392971132976
Item Name:	Milo XL I Anthracite 3000K
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	1000
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Replaceable LED by professional, Replaceable Control gear by professional
LED Colour:	Warm White
Colour Temperature (K):	3000
Colour Rendering Index (Ra):	>80
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	1600
Beam Angle (°):	45
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	L70 75000h Ta 25°C
Nominal Life Time (h):	75000
Lumen maintenance 50 000h:	L81
Lumen maintenance 75 000h:	L70
LLMF @ 50 000h:	0.81
Life Time Driver:	50 000h/10%
Flicker (PstLM):	0,05
Stroboscopic effect (SVM):	0,02

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60
Power LED (W):	8,4
Max. Power Luminaire (W):	10,5
Max. System Power (W):	10,5
Max. Efficiency Luminaire (lm/W):	95,2
Max. Efficiency System (lm/W):	95,2

Containing light source energy efficiency class (EU) 2019/2015: E

OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	OnOff
Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm2):	3x0,5-2,5
Through Wiring:	Yes
Strain Relief:	Yes
Min. Ta (°C):	-20
Max. Ta (°C):	40
Max. Tc (°C):	80
Fuse B10 (pcs):	46
Fuse B16 (pcs):	74
Fuse C10 (pcs):	93
Fuse C16 (pcs):	149

COLOR AND MATERIAL

Material:	Aluminium
Color:	Antracit
Environmental Assessment:	Byggvarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	55
Protection Class:	I
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK06
Width (mm):	82
Height (mm):	116
Depth (mm):	144
Diameter (mm):	100
Weight (kg):	0,96

