



MILO XL II GREY 3000K

Wall-mounted luminaire in a timeless design with light emission both up and down. LED COB with reflector optics and well-conceived design provides a good light spread and good luminous comfort. Separate rear element with dual cable bushings and push-in, loop-in, loop-out terminal block for easy installation. IP55 design with anodised and powder-coated housing for rough outdoor climate. Comes with built-in driver and spacers for surface-mounted cable routing.

DESCRIPTION

| | |
|-------------------|-----------------------|
| GTIN: | 7392971132983 |
| Item Name: | Milo XL II Grey 3000K |
| Warranty: | 5 years |
| Type: | . |

LIGHT TECHNICAL DATA

| | |
|-------------------------------------|---|
| Max. Luminaire Lumen (lm): | 2000 |
| Light Source: | LED |
| Light Source Included: | Yes |
| Replaceability: | Replaceable LED by professional, Replaceable Control gear by professional |
| LED Colour: | Warm White |
| Colour Temperature (K): | 3000 |
| Colour Rendering Index (Ra): | >80 |
| Colour Consistency (SDCM): | 3 |
| Luminous Intensity (cd): | 2x1600 |
| Beam Angle (°): | 45 |
| Light sharing: | Symmetric |
| Light Outlet: | Direct |
| Number of Lamps (pcs): | 2 |
| Number of LED (pcs): | 2 |
| Life Time: | h Ta °C |
| Nominal Life Time (h): | 75000 |
| Lumen maintenance 50 000h: | L81 |
| Lumen maintenance 75 000h: | L70 |
| LLMF @ 50 000h: | 0.81 |
| Life Time Driver: | 50 000h/10% |

TECHNICAL DATA

| | |
|-----------------------------------|------------|
| Voltage (type): | AC |
| Voltage Interval (V): | 220...240V |
| Voltage Nominal (V): | 230 |
| Line Frequency (Hz): | 50, 60 |
| Power LED (W): | 16,8 |
| Max. Power Luminaire (W): | 19,5 |
| Max. System Power (W): | 19,5 |
| Max. Efficiency Luminaire (lm/W): | 105 |
| Max. Efficiency System (lm/W): | 105 |

Containing light source energy efficiency class (EU) 2019/2015: E

OPERATION AND CONNECTION

| | |
|--------------------|------------------|
| Dimmable: | No |
| Type of Dimming: | OnOff |
| Driver Included: | Yes |
| Driver Model: | Constant Current |
| Driver Type: | Built-in |
| Connection (type): | Quick Terminal |
| Connection (mm2): | 3x0,5-2,5 |
| Through Wiring: | Yes |
| Strain Relief: | Yes |
| Min. Ta (°C): | -20 |
| Max. Ta (°C): | 40 |
| Max. Tc (°C): | 80 |
| Fuse B10 (pcs): | 4 |
| Fuse B16 (pcs): | 6 |
| Fuse C10 (pcs): | 14 |
| Fuse C16 (pcs): | 22 |

COLOR AND MATERIAL

| | |
|---------------------------|---------------------|
| Material: | Aluminium |
| Color: | Grey |
| Environmental Assessment: | Byggvarubedömningen |

MEASUREMENT AND INSTALLATION

| | |
|--------------------------|---------------------------------|
| Operating Environment: | Indoor / wet locations, Outdoor |
| IP Degree of Protection: | 55 |
| Protection Class: | I |
| Installation: | Surface mounted |
| Mounting Installation: | Screw Mounting |
| Approval Marks: | CE |
| Impact Strength: | IK06 |
| Width (mm): | 82 |
| Height (mm): | 232 |
| Depth (mm): | 144 |
| Diameter (mm): | 100 |
| Weight (kg): | 1,402 |

