



MILO I GU10 GREY

Wall-mounted luminaire with timeless design with downward light emission. GU10 socket allowing the selection of colour temperature and luminous intensity. Separate rear element with dual cable bushings and push-in, loop-in, loop-out terminal block for easy installation. IP55 design with anodised and powder-coated housing for rough outdoor climate. Delivered with spacers for surface-mounted cable routing.

DESCRIPTION

GTIN:	7392971133010
Item Name:	Milo I GU10 Grey
Warranty:	5 years
Type:	.

LIGHT TECHNICAL DATA

Lamp Holder (type):	GU10
Light sharing:	Symmetric
Light Outlet:	Direct
Life Time:	h Ta °C

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230

OPERATION AND CONNECTION

Dimmable:	Yes
Driver Included:	No
Connection (type):	Quick Terminal
Connection (mm2):	3x0,5-2,5
Through Wiring:	Yes
Strain Relief:	Yes
Power Interval for Catalogue (W):	50
Min. Ta (°C):	-20
Max. Ta (°C):	40

COLOR AND MATERIAL

Material:	Aluminium
Color:	Grey

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	55
Protection Class:	I
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK06
Width (mm):	82
Height (mm):	150
Depth (mm):	112
Diameter (mm):	68
Weight (kg):	0,593

