



## MILO II GU10 WHITE

Wall-mounted luminaire in a timeless design with light emission both up and down. GU10 socket allowing the selection of colour temperature and luminous intensity. Separate rear element with dual cable bushings and push-in, loop-in, loop-out terminal block for easy installation. IP55 design with anodised and powder-coated housing for rough outdoor climate. Delivered with spacers for surface-mounted cable routing.

### DESCRIPTION

<b>GTIN:</b>	7392971133034
<b>Item Name:</b>	Milo II GU10 White
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Lamp Holder (type):</b>	GU10
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Direct
<b>Life Time:</b>	h Ta °C

### TECHNICAL DATA

<b>Voltage (type):</b>	AC
<b>Voltage Interval (V):</b>	220...240V
<b>Voltage Nominal (V):</b>	230

### OPERATION AND CONNECTION

<b>Dimmable:</b>	Yes
<b>Driver Included:</b>	No
<b>Connection (type):</b>	Quick Terminal
<b>Connection (mm2):</b>	3x0,5-2,5
<b>Through Wiring:</b>	Yes
<b>Strain Relief:</b>	Yes
<b>Max. Power (W):</b>	50
<b>Min. Ta (°C):</b>	-20
<b>Max. Ta (°C):</b>	40

## COLOR AND MATERIAL

Material:	Aluminium
Color:	White

## MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	55
Protection Class:	I
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK06
Width (mm):	82
Height (mm):	190
Depth (mm):	112
Diameter (mm):	68
Weight (kg):	0,68

