



MILO II GU10 ANTHRACITE

Wall-mounted luminaire in a timeless design with light emission both up and down. GU10 socket allowing the selection of colour temperature and luminous intensity. Separate rear element with dual cable bushings and push-in, loop-in, loop-out terminal block for easy installation. IP55 design with anodised and powder-coated housing for rough outdoor climate. Delivered with spacers for surface-mounted cable routing.

DESCRIPTION

| | |
|-------------------|-------------------------|
| GTIN: | 7392971133058 |
| Item Name: | Milo II GU10 Anthracite |
| Warranty: | 5 years |
| Type: | . |

LIGHT TECHNICAL DATA

| | |
|----------------------------|-----------|
| Lamp Holder (type): | GU10 |
| Light sharing: | Symmetric |
| Light Outlet: | Direct |
| Life Time: | h Ta °C |

TECHNICAL DATA

| | |
|------------------------------|------------|
| Voltage (type): | AC |
| Voltage Interval (V): | 220...240V |
| Voltage Nominal (V): | 230 |

OPERATION AND CONNECTION

| | |
|--|----------------|
| Dimmable: | Yes |
| Driver Included: | No |
| Connection (type): | Quick Terminal |
| Connection (mm2): | 3x0,5-2,5 |
| Through Wiring: | Yes |
| Strain Relief: | Yes |
| Power Interval for Catalogue (W): | 50 |
| Min. Ta (°C): | -20 |
| Max. Ta (°C): | 40 |

COLOR AND MATERIAL

| | |
|-----------|-----------|
| Material: | Aluminium |
| Color: | Antracit |

MEASUREMENT AND INSTALLATION

| | |
|--------------------------|---------------------------------|
| Operating Environment: | Indoor / wet locations, Outdoor |
| IP Degree of Protection: | 55 |
| Protection Class: | I |
| Installation: | Surface mounted |
| Mounting Installation: | Screw Mounting |
| Approval Marks: | CE |
| Impact Strength: | IK06 |
| Width (mm): | 82 |
| Height (mm): | 190 |
| Depth (mm): | 112 |
| Diameter (mm): | 68 |
| Weight (kg): | 0,68 |

