



CONE ANTHRACITE

A neat wall fixture with a clean conical design. LED COB with reflector optics providing an asymmetrical light spread that lights up the wall and the ground below. Simple installation thanks to separate rear element with dual cable bushings and push-in terminal block for through wiring. Spacers for surface-mounted cable routing included. IP54 rated with durable powder coating for tough environments. Integrated driver with adjustable light level via DIP-Switch Power.

DESCRIPTION

GTIN:	7392971133102
Item Name:	Cone Anthracite
Warranty:	5 years
Type:	.

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	250
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Non-replaceable LED, Replaceable Control gear by professional
LED Colour:	Warm White
Colour Temperature (K):	3000
Colour Rendering Index (Ra):	>80
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	196
Beam Angle (°):	45
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	h Ta °C
Nominal Life Time (h):	80000
Life Time Driver:	50 000h/10%

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50
Power LED (W):	2,7
Max. Power Luminaire (W):	3
Max. System Power (W):	3
Max. Efficiency Luminaire (lm/W):	83
Max. Efficiency System (lm/W):	83

Containing light source energy efficiency class (EU) 2019/2015: F

OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	DIP 60% 100%, DIP-Switch Power
Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm2):	5x0,75-2,5
Through Wiring:	Yes
Strain Relief:	Yes
Power Factor λ :	0,5
Efficiency (%):	65
Standby Power:	1,6
Constant Current (mA):	300
Min. Ta (°C):	-20
Max. Ta (°C):	50
Max. Tc (°C):	80
Fuse B10 (pcs):	340
Fuse B16 (pcs):	573
Fuse C10 (pcs):	413
Fuse C16 (pcs):	653

COLOR AND MATERIAL

Material:	Aluminium
Color:	Antracit
Environmental Assessment:	Byggvarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	54
Protection Class:	I
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK09
Filament Test IEC 695-2-1(°C):	650
Width (mm):	105
Height (mm):	140
Depth (mm):	135
Diameter (mm):	105
Weight (kg):	0,64



