



## CONE ANTHRACITE

A neat wall fixture with a clean conical design. LED COB with reflector optics providing an asymmetrical light spread that lights up the wall and the ground below. Simple installation thanks to separate rear element with dual cable bushings and push-in terminal block for through wiring. Spacers for surface-mounted cable routing included. IP54 rated with durable powder coating for tough environments. Integrated driver with adjustable light level via DIP-Switch Power.

### DESCRIPTION

<b>GTIN:</b>	7392971133102
<b>Item Name:</b>	Cone Anthracite
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	250
<b>Light Source:</b>	LED
<b>Light Source Included:</b>	Yes
<b>Replaceability:</b>	Non-replaceable LED, Replaceable Control gear by professional
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>80
<b>Colour Consistency (SDCM):</b>	3
<b>Luminous Intensity (cd):</b>	196
<b>Beam Angle (°):</b>	45
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Direct
<b>Number of Lamps (pcs):</b>	1
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	L70 80000h Ta 25°C
<b>Nominal Life Time (h):</b>	80000
<b>Life Time Driver:</b>	50 000h/10%

## TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50
Power LED (W):	2,7
Max. Power Luminaire (W):	3
Max. System Power (W):	3
Max. Efficiency Luminaire (lm/W):	83,3
Max. Efficiency System (lm/W):	83,3

Containing light source energy efficiency class (EU) 2019/2015: F

## OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	DIP 60% 100%, DIP-Switch Power
Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm2):	5x0,75-2,5
Through Wiring:	Yes
Strain Relief:	Yes
Power Factor $\lambda$ :	0,5
Efficiency (%):	65
Standby Power:	1,6
Constant Current (mA):	300
Min. Ta (°C):	-20
Max. Ta (°C):	50
Max. Tc (°C):	80
Fuse B10 (pcs):	340
Fuse B16 (pcs):	573
Fuse C10 (pcs):	413
Fuse C16 (pcs):	653

## COLOR AND MATERIAL

Material:	Aluminium
Color:	Antracit
Environmental Assessment:	Byggvarubedömningen

## MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	54
Protection Class:	I
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK09
Filament Test IEC 695-2-1(°C):	650
Width (mm):	105
Height (mm):	140
Depth (mm):	135
Diameter (mm):	105
Weight (kg):	0,64



