



CONE GREY

A neat wall fitting with GU10 socket with a clean conical design providing an asymmetrical light spread that lights up the wall and the ground below. Simple installation thanks to separate rear element with dual cable bushings and push-in terminal block for through wiring. Spacers for surface-mounted cable routing included. IP54 rated with durable powder coating for tough environments in white, grey or anthracite. The light source can be selected for customised color temperature and luminous intensity.

DESCRIPTION

| | |
|------------|---------------|
| GTIN: | 7392971133126 |
| Item Name: | Cone Grey |
| Warranty: | 5 years |
| Type: | . |

LIGHT TECHNICAL DATA

| | |
|---------------------|---------|
| Lamp Holder (type): | GU10 |
| Life Time: | h Ta °C |

TECHNICAL DATA

| | |
|----------------------|-----|
| Voltage (type): | AC |
| Voltage Nominal (V): | 230 |

OPERATION AND CONNECTION

| | |
|-----------------------------------|----------------|
| Dimmable: | Yes |
| Driver Included: | No |
| Connection (type): | Quick Terminal |
| Connection (mm2): | 5x0,75-2,5 |
| Through Wiring: | Yes |
| Strain Relief: | Yes |
| Power Interval for Catalogue (W): | 50 |

COLOR AND MATERIAL

| | |
|-----------|-----------|
| Material: | Aluminium |
| Color: | Grey |

MEASUREMENT AND INSTALLATION

| | |
|---------------------------------|---------------------------------|
| Operating Environment: | Indoor / wet locations, Outdoor |
| IP Degree of Protection: | 54 |
| Protection Class: | I |
| Installation: | Surface mounted |
| Mounting Installation: | Screw Mounting |
| Approval Marks: | CE |
| Impact Strength: | IK09 |
| Width (mm): | 105 |
| Height (mm): | 140 |
| Depth (mm): | 135 |
| Weight (kg): | 0,54 |

