



## CUBE XL II WHITE 3000K

Impact resistant wall luminaire in cube-shaped timeless design for illumination of larger facades and entrances. Big brother in the Cube family. Easily installed and ready for direct connection to 230V. Simple installation thanks to separate rear element and push-in, loop-in, loop-out terminal block. Spacers for surface-mounted cable routing included. IP65 rating and durable powder coating for tough environments. Integrated driver with separate adjustable light level via DIP-Switch Power for up or downlight, 60% and 100%.

### DESCRIPTION

<b>GTIN:</b>	7392971135755
<b>Item Name:</b>	Cube XL II White 3000K
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	1890
<b>Light Source:</b>	LED
<b>Light Source Included:</b>	Yes
<b>Replaceability:</b>	Non-replaceable LED, Replaceable Control gear by professional
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>80
<b>Colour Consistency (SDCM):</b>	3
<b>Luminous Intensity (cd):</b>	617
<b>Beam Angle (°):</b>	80
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Direct
<b>Number of Lamps (pcs):</b>	2
<b>Number of LED (pcs):</b>	2
<b>Life Time:</b>	L70 75000h Ta 25°C
<b>Nominal Life Time (h):</b>	75000
<b>Life Time Driver:</b>	50 000h/10%
<b>Flicker (PstLM):</b>	0,023
<b>Stroboscopic effect (SVM):</b>	0,012

## TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50
Power LED (W):	21,6
Max. Power Luminaire (W):	25
Max. System Power (W):	25
Max. Efficiency Luminaire (lm/W):	75,6
Max. Efficiency System (lm/W):	75,6
Containing light source energy efficiency class (EU) 2019/2015: C	
Eprel registration number:	1071468

## OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	DIP 60% 100%, DIP-Switch Power
Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm2):	3x0,5-2,5
Through Wiring:	Yes
Constant Current (mA):	180, 300
Min. Ta (°C):	-20
Max. Ta (°C):	50
Max. Tc (°C):	80
Fuse B10 (pcs):	12
Fuse B16 (pcs):	21
Fuse C10 (pcs):	14
Fuse C16 (pcs):	23

## COLOR AND MATERIAL

Material:	Aluminium
Color:	White
Environmental Assessment:	Byggvarubedömningen

## MEASUREMENT AND INSTALLATION

Operating Environment:	Outdoor
IP Degree of Protection:	65
Protection Class:	I
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK10
Width (mm):	150
Height (mm):	150
Depth (mm):	150
Weight (kg):	3,13

