hidealite | Elektro Elco AB Tallvägen 5, 564 35 Bankeryd, Sweden
Phone + 46(0)36 290 60 00 | info@elco.se | www.hidealite.com





# STEPLIGHT GARDEN

Decorative step lighting with low energy consumption. Create striking staircase lighting, for example on patios and decks. Comes with 2×0.5 m rubber cables with screw connections. As an accessory there is also a transformer and 1 or 5 meter extension cables. Can be combined with Spotlight Garden and Decklight Garden thanks to the common coupling system.

## DESCRIPTION

| | |
|---|---|
| **GTIN:** | 7392971133140 |
| **Item Name:** | Steplight Garden |
| **Warranty:** | 5 years |

## LIGHT TECHNICAL DATA

| | |
|---|---|
| **Max. Luminaire Lumen (lm):** | 3 |
| **Light Source:** | LED |
| **Replaceability:** | Non-replaceaable LED |
| **LED Colour:** | Warm White |
| **Colour Temperature (K):** | 3000 |
| **Colour Rendering Index (Ra):** | >80 |
| **Colour Consistency (SDCM):** | 3 |
| **Light sharing:** | Asymmetric |
| **Light Outlet:** | Direct |
| **Number of Lamps (pcs):** | 1 |
| **Number of LED (pcs):** | 1 |
| **Life Time:** | L70 50 000h Ta 25°C |
| **Nominel Life Time (h):** | 50000 |
| **Lumen maintenance 50 000h:** | L70 |
| **LLMF @ 50 000h:** | 0.7 |

## TECHNICAL DATA

| | |
|---|---|
| **Voltage (type):** | DC |
| **Voltage Interval (V):** | 12...12V |
| **Voltage Nominal (V):** | 12 |
| **Voltage Forward (Vf):** | 9 |
| **Max. Power Luminaire (W):** | 0,8 |
| **Max. System Power (W):** | 0,8 |
| **Max. Efficiency Luminaire (lm/W):** | 3,8 |
| **Max. Efficiency System (lm/W):** | 3,8 |

## OPERATION AND CONNECTION

| | |
|---|---|
| **Dimmable:** | No |
| **Type of Dimming:** | OnOff |
| **Driver Included:** | No |
| **Driver Model:** | Constant Voltage |
| **Connection (type):** | Screw Connection, Cable |
| **Length Connection (cm):** | 50 |
| **Connection (mm2):** | 2x0,5 |
| **Through Wiring:** | Yes |
| **Operating Temperature:** | -25...+45°C |
| **Max. Tc (°C):** | 80 |

## COLOR AND MATERIAL

| | |
|---|---|
| **Material:** | Aluminium |
| **Color:** | Aluminum |

## MEASUREMENT AND INSTALLATION

| | |
|---|---|
| **Operating Environment:** | Outdoor |
| **IP Degree of Protection:** | 67 |
| **Protection Class:** | III |
| **Installation:** | Built-in |
| **Mounting Installation:** | Tension Spring |
| **Max. Pressure (kg):** | 100 |
| **Approval Marks:** | CE |
| **Height (mm):** | 34 |
| **Diameter (mm):** | 36 |
| **Weight (kg):** | 0,07 |
| **Min. Built-in (mm):** | Ø28x25 |
| **Height Recessed Part (mm):** | 23 |
| **Height Exterior Part (mm):** | 13 |
| **Built-in Ø (mm):** | 28mm |





