



LEDSTRIP RXM IP20 24V 3000K LPM

Flexible LEDstrip only 3.5 mm wide, high lumen output and very good colour rendering, Ra>90. Made for most indoor applications where an even lumen output is desired. Can be fitted in our aluminium profiles Micro U or Micro T. Comes as standard in rolls of five metres with 2m 2 m connecting cable at each end and self-adhesive tape for easy installation. Also available made to measure in optional lengths. Upon request, running meters with connection cables are delivered according to your specifications; running meters are delivered as standard without connection cables. Drivers are ordered separately according to required dimmer technology and placing.

DESCRIPTION

GTIN:	7392971129815
Item Name:	LEDstrip RXM IP20 24V 3000K lpm
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	510
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Non-replaceable LED
LED Colour:	Warm White
Colour Temperature (K):	3000
Colour Rendering Index (Ra):	>90
Colour Consistency (SDCM):	5
Luminous Intensity (cd):	160
Beam Angle (°):	120
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	120
LED Pitch (mm):	8
Life Time:	L70 50000h Ta 25°C
Nominal Life Time (h):	50000

TECHNICAL DATA

Voltage (type):	DC
Voltage Interval (V):	24...24V
Voltage Nominal (V):	24
Line Frequency (Hz):	50, 60
Power LED (W):	7,2
Max. Power Luminaire (W):	7,2
Max. System Power (W):	7,92
Max. Efficiency Luminaire (lm/W):	70,8
Max. Efficiency System (lm/W):	64,4
Energy Efficiency Class (EU) 2019/2015:	G
Eprel registration number:	931314

OPERATION AND CONNECTION

Dimmable:	Yes
Driver Included:	No
Driver Model:	Constant Voltage
Min. Ta (°C):	-20
Max. Ta (°C):	45
Max. Tc (°C):	85

COLOR AND MATERIAL

Material:	Copper
Color:	White
Environmental Assessment:	Byggvarubedömningen


MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	III
Installation:	Surface mounted
Mounting Installation:	Self Adhesive Tape
Approval Marks:	CE
Length (mm):	1000
Width (mm):	4
Height (mm):	2
Weight (kg):	0,02


LEDSTRIPS

Min. Bend Radius (mm):	60
Min. Length (m):	0,05
Max. Length (m):	5
Cutting Increments (mm):	50





(mm)



Hide-a-lite

7502860



7
kWh/1000h



2019/2015

