



LEDSTRIP 24V IP67 MIDLUM 4000K 5M

Basic version of our 24V LEDstrip, with 120 LED/m there is lots of light and good efficiency. The smaller gap between diodes gives a homogeneous light with opal cover also in lower profiles. Comes in 5m lengths with self-adhesive tape, 2m connecting cable at each end, 2 x 10stpcs 10cm shrink hoses, 10pcs clips and 20pcs screws. Also available made to measure in optional lengths with 50mm cut-off intervals and maximum length 10m. Drivers are ordered separately according to required dimmer technology and placing.

DESCRIPTION

GTIN:	7392971141978
Item Name:	LEDstrip 24V IP67 Midlum 4000K 5m
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	5200
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Non-replaceable LED
LED Colour:	White
Colour Temperature (K):	4000
Colour Rendering Index (Ra):	>90
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	330
Beam Angle (°):	120
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	600
LED Pitch (mm):	8
Life Time:	h Ta °C
Nominal Life Time (h):	50000
Lumen maintenance 50 000h:	L77
Lumen maintenance 75 000h:	L71
LLMF @ 50 000h:	0.77

TECHNICAL DATA

Voltage (type):	DC
Voltage Interval (V):	24...24V
Voltage Nominal (V):	24
Voltage Forward (Vf):	3
Max. Power Luminaire (W):	60
Max. System Power (W):	66
Max. Efficiency Luminaire (lm/W):	87
Max. Efficiency System (lm/W):	79
Energy Efficiency Class (EU) 2019/2015:	F

OPERATION AND CONNECTION

Dimmable:	Yes
Driver Included:	No
Driver Model:	Constant Voltage
Connection (type):	Cable
Length Connection (cm):	200
Connection (mm ²):	2x0,5
Min. Ta (°C):	-20
Max. Ta (°C):	45
Max. Tc (°C):	75

COLOR AND MATERIAL


Material:	Copper
Color:	White
Environmental Assessment:	Byggvarubedömningen

MEASUREMENT AND INSTALLATION


Operating Environment:	Indoor / bathroom (ceiling area 1), Outdoor
IP Degree of Protection:	67
Protection Class:	III
Installation:	Surface mounted
Mounting Installation:	Clips, Self Adhesive Tape
Approval Marks:	CE
Requires cooling:	No
Length (mm):	5000
Width (mm):	10
Height (mm):	6
Weight (kg):	0,56

LEDSTRIPS

Min. Bend Radius (mm):	30
Min. Length (m):	0,05
Max. Length (m):	10
Cutting Increments (mm):	50



included



Hide-a-lite

7507433



60
kWh/1000h

