



LED-DRIVER VSTR 24VDC 120W

DESCRIPTION

GTIN:	7392971123639
Item Name:	LED-driver VSTR 24VDC 120W
Warranty:	5 years

LIGHT TECHNICAL DATA

Flicker (PstLM):	0,101
Stroboscopic effect (SVM):	0,009

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Push 230V, 1-10V, DMX
Driver Model:	Constant Voltage
Driver Type:	Stand Alone
Connection (type):	Quick Terminal
Connection (mm2):	3x0,5-2,5
Strain Relief:	Yes
Connection Secondary (type):	Quick Terminal
Secondary Connection (mm2):	4x0,5-2,5
Secondary Outputs (pair):	3
Power Interval for Catalogue (W):	0-120
Max. Power (W):	120
Max. Load Per Output (W):	100
Min. Ta (°C):	-25
Max. Ta (°C):	50
Max. Tc (°C):	75
Memory Function Power Failure:	Yes
Protection Against:	Short Circuit, Overload, Overheating 100°C
Fuse B10 (pcs):	5
Fuse B16 (pcs):	8
Fuse C10 (pcs):	8
Fuse C16 (pcs):	13

COLOR AND MATERIAL

Color:	White
Environmental Assessment:	Byggvarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	I
Installation:	Surface mounted
Fire Safety Marks:	MM-mark
Approval Marks:	CE
Length (mm):	240
Width (mm):	60
Height (mm):	49
Weight (kg):	0,32
Built-in Ø (mm):	80mm



