



KLOSS

Compact and versatile LED luminaire with On/Off switch for both sliding and hinged doors in wardrobes, store rooms, closets, etc. The wardrobe luminaire has been given new life with modern LED technology. Simple installation thanks to separate rear element with dual cable bushings and removable push-in, loop-in, loop-out terminal block. Knockouts for surface-mounted cable routing and flex hose. This luminaire has an integrated 230V LED module for simple installation.

DESCRIPTION

GTIN:	7392971134321
Item Name:	Kloss
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	600
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Non-replaceable LED and control gear
LED Colour:	Warm White
Colour Temperature (K):	3000
Colour Rendering Index (Ra):	>80
Colour Consistency (SDCM):	4
Luminous Intensity (cd):	160
Beam Angle (°):	120
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	30
Life Time:	h Ta °C
Nominal Life Time (h):	50000
Lumen maintenance 50 000h:	L73
LLMF @ 50 000h:	0.73
Flicker (PstLM):	0,038
Stroboscopic effect (SVM):	0

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Power LED (W):	5
Max. Power Luminaire (W):	6,5
Max. System Power (W):	6,5
Max. Efficiency Luminaire (lm/W):	100
Max. Efficiency System (lm/W):	100
Containing light source energy efficiency class (EU) 2019/2015: E	

OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	OnOff
Connection (type):	Quick Terminal
Connection (mm ²):	3x0,5-1,5
Through Wiring:	Yes
Strain Relief:	Yes
Standby Power:	0
Min. Ta (°C):	-20
Max. Ta (°C):	40
Max. Tc (°C):	85

COLOR AND MATERIAL

Material:	ABS plastic
Material Housing/Enclosure:	Polycarbonate
Color:	White
Environmental Assessment:	Byggarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Surface mounted
Mounting Installation:	Screw Mounting
Fire Safety Marks:	MM-mark
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Length (mm):	140
Height (mm):	58
Depth (mm):	55
Weight (kg):	0,151



