



## CORE SMART TILT 45° WHITE 3000K

Small, exclusive accent luminaire of the highest quality for indoor use – tiltable 30°. Beautiful decor lighting for installation in niches and ceilings where the light needs to be directed. Recessed light point makes the luminaire glare free. Integrated push-in terminal for simplified and smart series connection, eliminates the hassle of external joints and minimises sources of faults and simplifies troubleshooting.

### DESCRIPTION

<b>GTIN:</b>	7392971139876
<b>Item Name:</b>	Core Smart Tilt 45° White 3000K
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	60
<b>Light Source:</b>	LED
<b>Replaceability:</b>	Non-replaceable LED
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>90
<b>Colour Consistency (SDCM):</b>	3
<b>Luminous Intensity (cd):</b>	95
<b>Beam Angle (°):</b>	45
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Direct
<b>Number of Lamps (pcs):</b>	1
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	h Ta °C
<b>Nominal Life Time (h):</b>	100000
<b>Lumen maintenance 50 000h:</b>	L94
<b>Lumen maintenance 75 000h:</b>	L91
<b>Lumen maintenance 100 000h:</b>	L88
<b>LLMF @ 50 000h:</b>	0.94
<b>LLMF @ 100 000h:</b>	0.88

## TECHNICAL DATA

Adjustable:	Yes
Tilttable (°):	30
Voltage Forward (Vf):	3
Max. Power Luminaire (W):	1,2
Max. System Power (W):	1,3
Max. Efficiency Luminaire (lm/W):	50
Max. Efficiency System (lm/W):	46,2
Containing light source energy efficiency class (EU) 2019/2015: E	
Eprel registration number:	1285858

## OPERATION AND CONNECTION

Dimmable:	Yes
Driver Included:	No
Driver Model:	Constant Current
Connection (type):	Quick Terminal
Connection (mm2):	2x0,2-0,75
Through Wiring:	Yes
Constant Current (mA):	350
Min. Ta (°C):	-20
Max. Ta (°C):	40
Max. Tc (°C):	80

## COLOR AND MATERIAL

Material:	Aluminium
Color:	White
Environmental Assessment:	Byggsvarubedömningen

## MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations, Indoor / bathroom (ceiling area 1)
IP Degree of Protection:	44
Protection Class:	III
Installation:	Built-in
Mounting Installation:	Tension Spring
Fire Safety Marks:	Not in insulation without protection cover
Protection Cover:	7466700, 7466701, 7466702
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Height (mm):	26
Diameter (mm):	40
Weight (kg):	0,02
Min. Built-in (mm):	Ø35x25
Height Recessed Part (mm):	24
Height Exterior Part (mm):	3
Built-in Ø (mm):	35mm



