



CORE SMART TILT 45° WHITE 3000K

Small, exclusive accent luminaire of the highest quality for indoor use – tiltable 30°. Beautiful decor lighting for installation in niches and ceilings where the light needs to be directed. Recessed light point makes the luminaire glare free. Integrated push-in terminal for simplified and smart series connection, eliminates the hassle of external joints and minimises sources of faults and simplifies troubleshooting.

DESCRIPTION

GTIN:	7392971139876
Item Name:	Core Smart Tilt 45° White 3000K
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	60
Light Source:	LED
Replaceability:	Non-replaceable LED
LED Colour:	Warm White
Colour Temperature (K):	3000
Colour Rendering Index (Ra):	>90
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	95
Beam Angle (°):	45
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	h Ta °C
Nominal Life Time (h):	100000
Lumen maintenance 50 000h:	L94
Lumen maintenance 75 000h:	L91
Lumen maintenance 100 000h:	L88
LLMF @ 50 000h:	0.94
LLMF @ 100 000h:	0.88

TECHNICAL DATA

Adjustable:	Yes
Tilttable (°):	30
Voltage Forward (Vf):	3
Max. Power Luminaire (W):	1,2
Max. System Power (W):	1,3
Max. Efficiency Luminaire (lm/W):	50
Max. Efficiency System (lm/W):	46,2
Containing light source energy efficiency class (EU) 2019/2015: E	
Eprel registration number:	1285858

OPERATION AND CONNECTION

Dimmable:	Yes
Driver Included:	No
Driver Model:	Constant Current
Connection (type):	Quick Terminal
Connection (mm2):	2x0,2-0,75
Through Wiring:	Yes
Constant Current (mA):	350
Min. Ta (°C):	-20
Max. Ta (°C):	40
Max. Tc (°C):	80

COLOR AND MATERIAL

Material:	Aluminium
Color:	White
Environmental Assessment:	Byggsvarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations, Indoor / bathroom (ceiling area 1)
IP Degree of Protection:	44
Protection Class:	III
Installation:	Built-in
Mounting Installation:	Tension Spring
Fire Safety Marks:	Not in insulation without protection cover
Protection Cover:	7466700, 7466701, 7466702
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Height (mm):	26
Diameter (mm):	40
Weight (kg):	0,02
Min. Built-in (mm):	Ø35x25
Height Recessed Part (mm):	24
Height Exterior Part (mm):	3
Built-in Ø (mm):	35mm



