



ACTOR G2 CEILING ASYM WHITE DALI CLO

Actor G2 Ceiling is a dimmable luminaire via traditional rotary/push dimmer or DALI, designed for surface mounting in fixed ceilings. Its clean, edge-aligned design blends seamlessly into the ceiling for a discreet look—ideal for spaces where the light should be visible but not dominant. The built-in DIP switch allows you to adjust the colour temperature directly on site. No need to plan everything in advance; the light can be fine-tuned after installation. The modular construction means you only replace the necessary part. Actor G2 Ceiling is perfect for corridors, entrances, and for wall or picture lighting. It can be installed individually, linked into continuous light lines, or arranged in patterns that follow the room's shape. Each luminaire acts as both leader and follower. For suspended mounting, a separate suspension kit is available, providing downlight only. Choose from a range of glare shields to adapt the light to the setting: opal, microprismatic, double parabolic or asymmetric or highlighting walls and artwork. Two cable entries at the bottom, and prepared for surface-mounted wiring at the ends.

DESCRIPTION

GTIN:	7392971155197
Item Name:	Actor G2 Ceiling Asym White DALI CLO
Warranty:	5 years

LIGHT TECHNICAL DATA

Min. Armaturlumen (lm):	2060
Max. Luminaire Lumen (lm):	2080
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Replaceable LED by professional
LED Colour:	White
Colour Temperature (K):	3000, 4000
Colour Rendering Index (Ra):	>90
Colour Consistency (SDCM):	3
Beam Angle (°):	50
Light sharing:	Asymmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Life Time:	h Ta °C
Nominal Life Time (h):	100000
Lumen maintenance 50 000h:	L100
Lumen maintenance 75 000h:	L100
Lumen maintenance 100 000h:	L100
LLMF @ 50 000h:	1
LLMF @ 100 000h:	1
Life Time Driver:	100 000h/10%
Flicker (PstLM):	0,0297
Stroboscopic effect (SVM):	0,0023

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60
Max. Power Luminaire (W):	19
Max. System Power (W):	19
Max. Efficiency Luminaire (lm/W):	109
Max. Efficiency System (lm/W):	109

Containing light source energy efficiency class (EU) 2019/2015: C

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	DALI 2, Push 230V
Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Driver Manufacturer:	TCI
Connection (type):	Quick Terminal
Connection (mm2):	5x0,75-2,5
Through Wiring:	Yes
Strain Relief:	Yes
Power Factor λ:	0,9
Efficiency (%):	89
Power loss (W):	0,5
Leakage current (mA) (at 230 V, 50 Hz, full load):	10
THD (%):	10
Standby Power:	0,5
Constant Current (mA):	400, 450, 500, 550
Min. Ta (°C):	0
Max. Ta (°C):	35
Max. Tc (°C):	80
Dimming secondary side:	AM
Memory Function Power Failure:	Yes
Protection Against:	Short Circuit, Overload
Inrush current (max/time):	5A 50 μ s
Mains surge protection DM (kV):	1
Mains surge protection CM (kV):	2
Fuse B10 (pcs):	22
Fuse B16 (pcs):	30
Fuse C10 (pcs):	32
Fuse C16 (pcs):	40

COLOR AND MATERIAL

Material:	Aluminium
Color:	White
Environmental Assessment:	EPD

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	I
Installation:	Surface mounted, Wall, Ceiling, System ceiling
Approval Marks:	CE
Length (mm):	1131
Width (mm):	52
Height (mm):	78
Weight (kg):	2,14



