



ACTOR G2 PENDANT MP WHITE DIM II LINK

Actor G2 Pendant is a suspended interior luminaire designed for easy installation and high visual comfort. Available in white or black powder-coated aluminium, it suits any modern environment. The suspension kit allows you to adjust the height effortlessly, and the built-in DIP switch lets you set both light distribution and colour temperature directly on site—quickly, precisely and without tools. No need to decide everything in advance; the light can be adjusted once the installation is complete. The design is modular, meaning you only replace the needed part—not the entire luminaire. It can be installed as a single unit or linked into long light lines. Choose between up/down light distribution of 30/70 or 50/50, depending on whether you want more work light downwards or ambient light upwards. The luminaire is available as dimmable via one or two pull cords, PIR with or without a pull cord, PIR with Casambi, and DALI. As an option for all versions, LINK luminaires and accessories such as L, T and X are available for building light lines and patterns. Select between opal, microprismatic or double parabolic glare shields. The double parabolic version meets screen and UGR requirements (UGR ≤ 19 for offices) under standard conditions. Delivered complete with ceiling mounting accessories, earthed cable set or 5-pole ALI cable with open ends.

DESCRIPTION

GTIN:	7392971154398
Item Name:	Actor G2 Pendant MP White DIM II LINK
Warranty:	5 years

LIGHT TECHNICAL DATA

Min. Armaturlumen (lm):	5300
Max. Luminaire Lumen (lm):	5800
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Replaceable LED by professional
LED Colour:	White
Colour Temperature (K):	3000, 4000
Colour Rendering Index (Ra):	>90
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	1800
Beam Angle (°):	80
Light sharing:	Symmetric
Light Outlet:	30/70, 50/50
Number of Lamps (pcs):	2
Number of LED (pcs):	288
Life Time:	h Ta °C
Nominal Life Time (h):	100000
Lumen maintenance 50 000h:	L90
Lumen maintenance 75 000h:	L85
Lumen maintenance 100 000h:	L80
LLMF @ 50 000h:	0.9
LLMF @ 100 000h:	0.8
Life Time Driver:	100 000h/10%
Flicker (PstLM):	0,0133
Stroboscopic effect (SVM):	0,0008

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60
Max. Power Luminaire (W):	41
Max. System Power (W):	41
Max. Efficiency Luminaire (lm/W):	141
Max. Efficiency System (lm/W):	141

Containing light source energy efficiency class (EU) 2019/2015: C

OPERATION AND CONNECTION

Dimmable:	Yes
Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Driver Manufacturer:	Hide-a-lite
Connection (type):	Quick Connection
Power Factor λ:	0,9
Efficiency (%):	89
Power loss (W):	41
Leakage current (mA) (at 230 V, 50 Hz, full load):	0,5
THD (%):	10
Constant Current (mA):	850
Min. Ta (°C):	0
Max. Ta (°C):	35
Max. Tc (°C):	80
Dimming secondary side:	Hybrid
Suitable for random switching:	Yes
Inrush current (max/time):	28A 100 μ s
Mains surge protection DM (kV):	1
Mains surge protection CM (kV):	2
Fuse B10 (pcs):	23
Fuse B16 (pcs):	28
Fuse C10 (pcs):	37
Fuse C16 (pcs):	45

COLOR AND MATERIAL

Material:	Aluminium
Color:	White
Environmental Assessment:	EPD

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	I
Installation:	Pendant
Approval Marks:	CE
Length (mm):	1201
Width (mm):	52
Height (mm):	78
Weight (kg):	2,24



