
hidealite | Fiskarsinkatu 3, 20750 TURKU, PL 9, 20101 Turku
Phone 0207 499 499 | info@hidealite.fi | www.hidealite.fi





LEDSTRIP 230V IP65 MIDLUM 2700K /M

Asennus ei voisi olla helpompaa – ei tarvita ohjaimia tai rajoittavia toisiopuolen kaapelointeja. LEDstrip 230V kytketään suoraan 230V, ja sen katkaisuväli on vain 10cm. LEDstrip 230V luo tasaisen valolinjan ilman katkoksia, ja sitä on saatavana kahdella valomäärällä, Mid ja High, jotka sopivat täydellisesti ulkokäyttöön (IP65). Asennus kiinteille ja vankoille pinnoille, kuten julkisivuihin ja räystäisiin. LEDstrip 230V on saatavana On/Off-versiona useissa värilämpötiloissa, ja se voidaan asentaa pituuksina 10 cm:stä aina 30 metriin, riippuen asennusalustasta. Sopii erinomaisesti useisiin alumiiniprofiileihimme. Näkyvässä asennuksessa suositellaan huurrettua kupua parhaan valaistuskokemuksen saavuttamiseksi. LEDstrip 230V toimitetaan vakiona 10 metrin rullissa, joissa on itsekiinnittyvä teippi, 3 metrin liitäntäkaapeli pistokkeella, kiinnitysklipsit sekä, liitäntä- ja päätykappaleet. Saatavana myös räätälöidyissä pituuksissa. Oletuksena metritavarana myytävä LED-nauha toimitetaan ilman liitosjohtoa. Pyydä tarjous LED-nauhasta haluamasi mittaisella liitosjohdolla varustettuna. Liitäntä-/jatkosarjat sekä kiinnitysklipsit ovat saatavana lisävarusteina ja ne tilataan erikseen.

TUOTEKUVAUS

SNRO:	4240483
Korvaa:	4240477
Item Name:	LEDstrip 230V IP65 MidLum 2700K /m
Takuu:	5 vuotta

VALAISUTIEDOT

Valomäärä (lm):	700
Valonlähde:	LED
Vaihdettavuus:	Non-replacaable LED
Valon väri:	Lämmin valkoinen
Värilämpötila (K):	2700
Värintoisto (Ra):	>80
Sallittu väripoikkeama (SDCM):	6
Valovoima (cd):	195
Hajontakulma (°):	120
Valon hajonta:	Symmetrinen
Valonjakauma:	Suora
Valolähteiden määrä (kpl):	1
LEDien määrä (kpl):	120
LED etäisyys (mm):	8
Käyttöikä:	L70 90 000h Ta 25°C
Nimellinen käyttöikä (h):	90000
Välkyntä (PstLM):	0,5

TEKNISET TIEDOT

Jännite (tyyp.):	AC
Jänniteväli (V):	220...240V
Nimellisjännite (V):	230
Verkkotaajuus (Hz):	50, 60
Kokonaisteho (W):	7
Järjestelmän teho (W):	7
Valaisimen tehokkuus (lm/W):	100
Järjestelmän tehokkuus lm/W:	100
Energiatehokkuusluokka (EU) 2019/2015:	E
Eprel rekiterinumero:	941598

KÄYTTÖ JA KYTKENTÄ

Himmennettävä:	Ei
Käyttölämpötila-alue Ta (°C):	-25...+40°C
Maks. Tc (°C):	80

VÄRI JA MATERIAALI


Materiaali:	Kupari, Silikoni
Väri:	Valkoinen
Environmental Assessment:	Byggvarubedömningen

MITAT JA ASENNUS

Käyttöympäristö:	Ulkotilat
IP-luokka:	65
Kotelointiluokka:	II
Asennus:	Pinta-asennus
Kiinnitys:	Klipsi, Itseliimautuva teippi
Hyväksyntämerkintä:	CE, VDE
Hehkulankatesti IEC 695-2-1 (°C):	650
Pituus (mm):	1000
Leveys (mm):	12
Korkeus (mm):	4
Paino (kg):	0,06

LISÄTIEDOT

Min. taivutussäde (mm):	50
Min. pituus (m):	0,1
Maks. pituus (m):	30
Katkaisuväli (mm):	100


















IMPORTANT FOR INSTALLING LEDSTRIPS
hidealite
Below are important general Installation Instructions for safe and correct installation of LEDstrips, including recommendations for mounting and handling.
General Installation Instructions
The installation should be performed by a qualified installer.
Always check the respective LEDstrip manual and visit hidealite.se for the correct installation instructions.
For outdoor installation, ensure that the LED strip does not end up in standing water.
Always check the respective LEDstrip manual before installation to ensure the correct maximum length.
Do not bend the LEDstrip beyond the allowed limit. Use an intermediate cable for corners.
Handle LED strips carefully to avoid damage.
Installation and Preparations
Make sure the power is switched off during installation and that the LEDstrips do not overlap to avoid overheating.
Clean the surface where the LEDstrip will be mounted with, for example, denatured alcohol (T-sprit) for the best adhesion.
Follow the cutting intervals carefully and make straight cuts.
Both ends of the LED strip should be glued or secured with silicone to ensure it stays in place over time.
All LEDstrips with a rating higher than IP20 must be properly sealed according to the manual for the product to meet its correct IP rating and to be covered by the warranty.
Lengths over 5 meters are recommended to be installed by two people to avoid twisting, which can damage the LED strip and its components.
Installation of the LED strip, wiring, and drivers should be easily accessible for maintenance.
Environmental and Sustainability Factors
It is important that the LED strips maximum specified ambient temperature is taken into consideration in order to guarantee its life span, if this is exceeded, the life span can be shortened drastically.
Carefully consider the appropriate placement of the LED strip for outdoor installations. Avoid areas that are hot and exposed to direct sunlight.
For outdoor installation in a profile, the profile should be able to move in at least one direction. Profiles longer than 4 meters should be installed with at least a 1mm gap to allow for movement as the material expands due to temperature fluctuations. In this gap, the LED strip should be complemented with silicone/adhesive (taped LED strips can be in one continuous length as the LED strip expands along with the profile).*
An aluminum profile is recommended for heat dissipation. The tape adheres best to an aluminum profile.
LED strips should be installed on fixed structures such as buildings, facades, permanent outdoor fixtures, fixed signs, and ceiling/wall niches.
When installing outdoors, obvious wind- and vibration-exposed environments should be avoided, e.g., bridges, open stair structures, and unstable signs.
When using our extension arms or mounting on wooden surfaces outdoors, the maximum lenght is 10m.
Version 2025/02/04


(mm)
3m
8
4
12
100


x100
x2
x50
x1
x1
3m


B


ENERG
Hide-a-lite
7505735
A
B
C
D
E
F
G
E
7
kWh/1000h
2019/2015

