



Q-BOX MULTI CASAMBI TED

Q-box Multi is our connection box for quickly connecting and controlling lighting via Casambi, which gives you full, direct control of the light via a simple app. The box is IP20 rated and intended for placement in suspended ceilings or surface-mounted indoor installations. The box can be attached with screws to any surface. Supplied with screws for mounting Casambi smart pucks and cabling for smooth connection between terminal block and puck. Strain relief for both cabling and hose, loop-in loop-out.

DESCRIPTION

GTIN:	7392971152707
Item Name:	Q-Box Multi Casambi TED
Warranty:	5 years

TECHNICAL DATA

Adjustable:	No
Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Casambi LR, Trailing Edge
Connection (type):	Quick Terminal
Connection (mm2):	5x0,5-2,5
Through Wiring:	Yes
Strain Relief:	Yes
Connection Secondary (type):	Quick Terminal, Cable
Length Connection Secondary (cm):	15
Secondary Connection (mm2):	4x0,5-1,5
Efficiency (%):	95
Power loss (W):	0,5
Power Interval for Catalogue (W):	1-100
Standby Power:	0,3
Current (A):	0,43
Min. Ta (°C):	-20
Max. Ta (°C):	40
Max. Tc (°C):	75
Memory Function Power Failure:	Yes
Protection Against:	Short Circuit, Overheating 90°C, Overload
Inrush current (max/time):	10A 100000µs

COLOR AND MATERIAL

Material:	Plastic
Color:	White

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Built-in, Surface mounted
Mounting Installation:	Screw Mounting
Fire Safety Marks:	Approved for installation against insulation
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Length (mm):	108
Width (mm):	110
Height (mm):	32
Weight (kg):	0,1
Built-in Ø (mm):	104mm



