hidealite | Elektro Elco AB Tallvägen 5, 564 35 Bankeryd, Sweden
Phone + 46(0)36 290 60 00 | info@elco.se | www.hidealite.com





LEDSTRIP 24V LINE IP67 MIDLUM 3000K 5M

Description

LED strip for an even and shadow-free light even without a cover. Delivered in a 5-meter roll with a 2-meter connection cable at both ends, self-adhesive tape, and accessories. Sold by the meter as standard without connection cable. Upon request, the LED strip can also be supplied by the meter with custom connection cables. Accessories and drivers are ordered separately for the desired dimming technology and placement.

Light Technical Data

Even light without visible dots. Luminous fluxes in Lowlum and Midlum for application adaptation. Available in 2700K, 3000K, and 4000K. Ra>90.

Technical data

Even light without visible dots. Luminous fluxes in Lowlum and Midlum for application adaptation. Available in 2700K, 3000K, and 4000K. Ra>90.

Measurement and installation

Easily mounts with self-adhesive tape on solid surfaces. Cutting interval 31 mm. Fits with several of our aluminum profiles.

DESCRIPTION

GTIN:	7392971153995
Item Name:	LEDstrip 24V Line IP67 Midlum 3000K 5m
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	4500
Light Source:	LED
Replaceability:	Non-replaceaable LED
LED Colour:	Warm White
Colour Temperature (K):	3000
Colour Rendering Index (Ra):	>90
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	1155
Beam Angle (°):	120
Light Outlet:	Direct
Number of LED (pcs):	1280
Life Time:	L70 75 000h Ta 25°C
Nominel Life Time (h):	75000
Lumen maintenance 50 000h:	L90
Lumen maintenance 75 000h:	L70
LLMF @ 50 000h:	0.9

TECHNICAL DATA

Voltage (type):	DC
Voltage Interval (V):	24...24V
Voltage Nominal (V):	24
Voltage Forward (Vf):	3
Power LED (W):	0,06
Max. Power Luminaire (W):	48
Max. System Power (W):	52,8
Max. Efficiency Luminaire (lm/W):	93,8
Max. Efficiency System (lm/W):	85,2
Energy Efficiency Class (EU) 2019/2015:	F
Eprel registration number:	2520460

OPERATION AND CONNECTION

Dimmable:	Yes
Driver Included:	No
Driver Model:	Constant Voltage
Connection (type):	Open Cable End
Length Connection (cm):	200
Connection (mm2):	2x0,75
Operating Temperature:	-20...+40°C
Max. Tc (°C):	60

COLOR AND MATERIAL

Material:	Copper, Silicone
Color:	White
Environmental Assessment:	EPD, Byggvarubedömningen

MEASUREMENT AND INSTALLATION

IP Degree of Protection:	67
Protection Class:	III
Installation:	Surface mounted
Mounting Installation:	Self Adhesive Tape
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Requires cooling:	No
Length (mm):	5000
Width (mm):	10
Height (mm):	5
Weight (kg):	0,28

LEDSTRIPS

Min. Bend Radius (mm):	50
Min. Length (m):	0,031
Max. Length (m):	6
Cutting Increments (mm):	31,25











