



## ROTARY DIMMER DALI SINGLE COLOR

DALI dimmer for LED and electronic drivers with DALI interface. The dimmer has integrated power supply. Can control a chosen DALI-group or work as broadcast. For 1-25 DALI devices. Up to four dimmers can be connected in parallel with synchronized control. Comes complete with frame and center plate, also fits frames from other brands. For further technical information see instruction manual.

### DESCRIPTION

<b>GTIN:</b>	7392971136790
<b>Item Name:</b>	Rotary dimmer DALI Single color
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Life Time Driver:</b>	50 000h/15%
--------------------------	-------------

### TECHNICAL DATA

<b>Voltage (type):</b>	AC
<b>Voltage Interval (V):</b>	110...240V
<b>Voltage Nominal (V):</b>	230
<b>Line Frequency (Hz):</b>	50, 60

### OPERATION AND CONNECTION

<b>Dimmable:</b>	Yes
<b>Type of Dimming:</b>	DALI, DALI DT6
<b>Driver Type:</b>	Built-in
<b>Connection (type):</b>	Screw Terminals
<b>Connection (mm2):</b>	2x0,5-2,5
<b>Connection Secondary (type):</b>	Screw Terminals
<b>Secondary Connection (mm2):</b>	2x0,5-2,5
<b>Standby Power:</b>	1
<b>Min. Ta (°C):</b>	0
<b>Max. Ta (°C):</b>	50
<b>Max. Tc (°C):</b>	50
<b>Memory Function Power Failure:</b>	Yes

## COLOR AND MATERIAL

Material:	Plastic
Color:	White
Environmental Assessment:	Byggvarubedömningen

## MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Built-in
Mounting Installation:	Screw Mounting
Fire Safety Marks:	MM-mark
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Length (mm):	80
Width (mm):	80
Height (mm):	53
Weight (kg):	0,2
Built-in Ø (mm):	73mm

