



ROTARY DIMMER DALI SINGLE COLOR

DALI dimmer for LED and electronic drivers with DALI interface. The dimmer has integrated power supply. Can control a chosen DALI-group or work as broadcast. For 1-25 DALI devices. Up to four dimmers can be connected in parallel with synchronized control. Comes complete with frame and center plate, also fits frames from other brands. For further technical information see instruction manual.

DESCRIPTION

GTIN:	7392971136790
Item Name:	Rotary dimmer DALI Single color
Warranty:	5 years

LIGHT TECHNICAL DATA

Life Time Driver:	50 000h/15%
--------------------------	-------------

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	110...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	DALI, DALI DT6
Driver Type:	Built-in
Connection (type):	Screw Terminals
Connection (mm2):	2x0,5-2,5
Connection Secondary (type):	Screw Terminals
Secondary Connection (mm2):	2x0,5-2,5
Standby Power:	1
Min. Ta (°C):	0
Max. Ta (°C):	50
Max. Tc (°C):	50

COLOR AND MATERIAL

Material:	Plastic
Color:	White
Environmental Assessment:	Byggvarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Built-in
Mounting Installation:	Screw Mounting
Fire Safety Marks:	MM-mark
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Length (mm):	80
Width (mm):	80
Height (mm):	53
Weight (kg):	0,2
Built-in Ø (mm):	73mm

