



STEPLIGHT GARDEN

Decorative step lighting with low energy consumption. Create striking staircase lighting, for example on patios and decks. Comes with 2×0.5 m rubber cables with screw connections. As an accessory there is also a transformer and 1 or 5 meter extension cables. Can be combined with Spotlight Garden and Decklight Garden thanks to the common coupling system.

DESCRIPTION

GTIN:	7392971133140
Item Name:	Steplight Garden
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	3
Light Source:	LED
Replaceability:	Non-replaceable LED
LED Colour:	Warm White
Colour Temperature (K):	3000
Colour Rendering Index (Ra):	>80
Colour Consistency (SDCM):	3
Light sharing:	Asymmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	L70 50000h Ta 25°C
Nominal Life Time (h):	50000
Lumen maintenance 50 000h:	L70
LLMF @ 50 000h:	0.7

TECHNICAL DATA

Voltage (type):	DC
Voltage Interval (V):	12...12V
Voltage Nominal (V):	12
Voltage Forward (Vf):	9
Max. Power Luminaire (W):	0,8
Max. System Power (W):	0,8
Max. Efficiency Luminaire (lm/W):	3,8
Max. Efficiency System (lm/W):	3,8

OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	OnOff
Driver Included:	No
Driver Model:	Constant Voltage
Connection (type):	Screw Connection, Cable
Length Connection (cm):	50
Connection (mm2):	2x0,5
Through Wiring:	Yes
Min. Ta (°C):	-25
Max. Ta (°C):	45
Operating Temperature:	-25...+45°C
Max. Tc (°C):	80

COLOR AND MATERIAL

Material:	Aluminium
Color:	Aluminum

MEASUREMENT AND INSTALLATION

Operating Environment:	Outdoor
IP Degree of Protection:	67
Protection Class:	III
Installation:	Built-in
Mounting Installation:	Tension Spring
Max. Pressure (kg):	100
Approval Marks:	CE
Height (mm):	34
Diameter (mm):	36
Weight (kg):	0,07
Min. Built-in (mm):	Ø28x25
Height Recessed Part (mm):	23
Height Exterior Part (mm):	13
Built-in Ø (mm):	28mm

