



## OPTIC TRACK S 36° WHITE 3000K

Dimmable tracklights with replaceable LED and driver – built for the future. With reflector technology, high luminous efficacy is ensured with distinct and clear light distribution – perfect as accent lighting when you want to direct the light onto what you want to highlight, but also as general lighting in both private and public environments. Low-build universal adapter for 3-phase track. For improved glare reduction, the Honeycomb accessory can be added to the luminaire. You can easily replace the reflector with a lens accessory to adjust the light distribution as needed (XS, XXS). Suitable for most 3-phase track systems, e.g. Global Trac, (Erco for phase dimming).

### DESCRIPTION

<b>GTIN:</b>	7392971140469
<b>Item Name:</b>	Optic Track S 36° White 3000K
<b>Warranty:</b>	5 years

## LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	1050
<b>Light Source:</b>	LED
<b>Light Source Included:</b>	Yes
<b>Replaceability:</b>	Replaceable LED by professional, Replaceable Control gear by professional
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>90
<b>Colour Consistency (SDCM):</b>	3
<b>Luminous Intensity (cd):</b>	2790
<b>Beam Angle (°):</b>	36
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Direct
<b>Number of Lamps (pcs):</b>	1
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	L80 100000h Ta 25°C
<b>Nominal Life Time (h):</b>	100000
<b>Lumen maintenance 50 000h:</b>	L91
<b>Lumen maintenance 75 000h:</b>	L87
<b>Lumen maintenance 100 000h:</b>	L83
<b>LLMF @ 50 000h:</b>	0.91
<b>LLMF @ 100 000h:</b>	0.83
<b>Life Time Driver:</b>	50 000h/10%
<b>Flicker (PstLM):</b>	0,03
<b>Stroboscopic effect (SVM):</b>	0,04

## TECHNICAL DATA

<b>Adjustable:</b>	Yes
<b>Tilttable (°):</b>	90
<b>Rotatable (°):</b>	355
<b>Voltage (type):</b>	AC
<b>Voltage Interval (V):</b>	220...240V
<b>Voltage Nominal (V):</b>	230
<b>Line Frequency (Hz):</b>	50, 60
<b>Power LED (W):</b>	10
<b>Max. Power Luminaire (W):</b>	12
<b>Max. System Power (W):</b>	12
<b>Max. Efficiency Luminaire (lm/W):</b>	87,5
<b>Max. Efficiency System (lm/W):</b>	87,5
<b>Containing light source energy efficiency class (EU) 2019/2015:</b>	F
<b>Eprel registration number:</b>	869651

## OPERATION AND CONNECTION

<b>Dimmable:</b>	Yes
<b>Type of Dimming:</b>	Trailing Edge
<b>Driver Included:</b>	Yes - replaceable
<b>Driver Model:</b>	Constant Current
<b>Driver Type:</b>	Built-in
<b>Connection (type):</b>	3-phase universal adapter
<b>Power Factor <math>\lambda</math>:</b>	0,92
<b>Efficiency (%):</b>	82
<b>Power loss (W):</b>	2,2
<b>Leakage current (mA) (at 230 V, 50 Hz, full load):</b>	0,25
<b>THD (%):</b>	20
<b>Constant Current (mA):</b>	300
<b>Min. Ta (°C):</b>	-20
<b>Max. Ta (°C):</b>	35
<b>Max. Tc (°C):</b>	78
<b>Dimming secondary side:</b>	AM
<b>Suitable for random switching:</b>	Yes
<b>Inrush current (max/time):</b>	10A 14 $\mu$ s
<b>Mains surge protection DM (kV):</b>	2
<b>Fuse B10 (pcs):</b>	30
<b>Fuse B16 (pcs):</b>	48
<b>Fuse C10 (pcs):</b>	50
<b>Fuse C16 (pcs):</b>	80

## COLOR AND MATERIAL

<b>Material:</b>	Aluminium
<b>Color:</b>	White
<b>Environmental Assessment:</b>	Byggvarubedömningen
<b>SCIP:</b>	55eb7e0c-2d7f-4eb8-a2f5-6cc230414122

## MEASUREMENT AND INSTALLATION

<b>Operating Environment:</b>	Indoor / dry locations
<b>IP Degree of Protection:</b>	20
<b>Protection Class:</b>	II
<b>Installation:</b>	Light-track mounting
<b>Mounting Installation:</b>	3-phase Universal Adapter
<b>Approval Marks:</b>	CE, a Hide-a-lite Choice
<b>Filament Test IEC 695-2-1(°C):</b>	650
<b>Length (mm):</b>	195
<b>Height (mm):</b>	153
<b>Diameter (mm):</b>	83
<b>Weight (kg):</b>	0,7




36°

3000K

m	∅ (m)	Lux Emed/Emax
1m	0,6	1900/2790
2m	1,1	480/700
3m	1,6	210/310
5m	2,7	80/110

2790cd



hideolite  
choice

We focus on sustainability using recycled material for creating innovative luminaires, as well as replaceable LEDs and drivers.

Luminaires built for the future!