



## LED-TRAFO SLT 12V 60W

DC transformer for 12V or 24V LED light sources. Protection against short circuiting, overloading and overheating with automatic restart.

### DESCRIPTION

GTIN:	7392971131719
Item Name:	LED-trafo SLT 12V 60W
Warranty:	5 years

### LIGHT TECHNICAL DATA

Life Time Driver:	35 000h/4%
-------------------	------------

### TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60

## OPERATION AND CONNECTION

<b>Dimmable:</b>	No
<b>Type of Dimming:</b>	OnOff
<b>Driver Model:</b>	Constant Voltage
<b>Driver Type:</b>	Stand Alone
<b>Connection (type):</b>	Screw Terminals
<b>Connection (mm2):</b>	2x0,75
<b>Strain Relief:</b>	Yes
<b>Connection Secondary (type):</b>	Screw Terminals
<b>Secondary Connection (mm2):</b>	2x0,75
<b>Secondary Outputs (pair):</b>	1
<b>Power Interval for Catalogue (W):</b>	0-60
<b>Max. Power (W):</b>	60
<b>Standby Power:</b>	0,3
<b>Current (A):</b>	0,3
<b>Min. Ta (°C):</b>	-20
<b>Max. Ta (°C):</b>	50
<b>Max. Tc (°C):</b>	90
<b>Protection Against:</b>	Short Circuit, Overheating 110°C, Overload
<b>Fuse B10 (pcs):</b>	9
<b>Fuse B16 (pcs):</b>	15
<b>Fuse C10 (pcs):</b>	15
<b>Fuse C16 (pcs):</b>	25

## COLOR AND MATERIAL

<b>Material:</b>	Plastic
<b>Color:</b>	White
<b>Environmental Assessment:</b>	Byggvarubedömningen

## MEASUREMENT AND INSTALLATION

<b>Operating Environment:</b>	Indoor / dry locations
<b>IP Degree of Protection:</b>	20
<b>Protection Class:</b>	II
<b>Installation:</b>	Surface mounted
<b>Mounting Installation:</b>	Screw Mounting
<b>Fire Safety Marks:</b>	MM-mark
<b>Approval Marks:</b>	CE, S
<b>Length (mm):</b>	175
<b>Width (mm):</b>	45
<b>Height (mm):</b>	30
<b>Weight (kg):</b>	0,23

